

DISABLE ALL SYMBOLOGY

This command is used to disable all symbologies.

Request Packet

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
FUNCTION_TYPE	Required	Static value	N/A	N/A	BARCODE	Type of function
COMMAND	Required	Static value	N/A	N/A	BCDISABLEALLSYMBOLOLOGIES	Command name
COUNTER	Required	Numeric	1	10		COUNTER is used for a given MAC label. Each COUNTER should be higher than the last one. This is used to authenticate the POS. Example: 7
MAC	Required	Base64 Encoded Data	N/A	N/A		Message Authentication Code. This is used to authenticate the POS.
MAC_LABEL	Required	Character	1	50		Associated label that tells the device which MAC_KEY to use to decrypt the value of MAC. This is used to authenticate the POS. Example: PJTY065

Example

Following is an example of request packet

```
<TRANSACTION>
<FUNCTION_TYPE>BARCODE</FUNCTION_TYPE>
<COMMAND>BCDISABLEALLSYMBOLOLOGIES</COMMAND>
<MAC>...</MAC>
<COUNTER>7</COUNTER>
```

```
<MAC_LABEL>P_JTY065</MAC_LABEL>
</TRANSACTION>
```

Response Packet

Field	Type	Value	Description
RESPONSE_TEXT	Character		Processor response text. Example: Command response 0
RESULT	Character		This indicates the Result details. Example: SUCCESS
RESULT_CODE	Numeric	Expected result code: -1, 59001, 59006, 59040	This indicates the result code. Refer to Result/Error Codes for details.
TERMINATION_STATUS	Character	SUCCESS or FAILURE	This indicates the transaction termination status. This is the overall status of the transaction irrespective of approved or declined. Like, if the output is generated then the status is SUCCESS and if no output is generated then the status will be FAILURE.
COUNTER	Numeric		Echoes counter sent in the request. Example: 7

Example

Following is an example of response packet

```
<RESPONSE>
<RESPONSE_TEXT>Command response 0</RESPONSE_TEXT>
<RESULT>SUCCESS</RESULT>
<RESULT_CODE>-1</RESULT_CODE>
<TERMINATION_STATUS>SUCCESS</TERMINATION_STATUS>
<COUNTER>7</COUNTER>
</RESPONSE>
```