

CUSTOMER_BUTTONS

This command directs the device to display up to five (5) lines of display text and up to six (6) on screen button selections with corresponding labels.

Device UI Required: Yes

Request Packet

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
FUNCTION_TYPE	Required	Static value	N/A	N/A	DEVICE	Type of function.
COMMAND	Required	Static value	N/A	N/A	CUST_BUTTON	Command name
DISPLAY_TEXT1	Optional	Character	1	45		Displays text line 1. Example: <i>PLEASE SELECT THE COMPANY</i>
DISPLAY_TEXT2	Optional	Character	1	45		Displays text line 2. Example: <i>YOU HAVE WORKED</i>
DISPLAY_TEXT3	Optional	Character	1	45		Displays text line 3. Example: <i>THROUGHOUT</i>
DISPLAY_TEXT4	Optional	Character	1	45		Displays text line 4. Example: <i>YOUR</i>
DISPLAY_TEXT5	Optional	Character	1	45		Displays text line 5. Example: <i>CAREER</i>
BUTTON_LABEL1	Optional	Character	1	15		Label for Button 1. Example: <i>WORLD MARKETING</i>
BUTTON_LABEL2	Optional	Character	1	15		Label for Button 2. Example: <i>VERIFONE</i>
BUTTON_LABEL3	Optional	Character	1	15		Label for Button 3. Example: <i>FIRSTDATA</i>
BUTTON_LABEL4	Optional	Character	1	15		Label for Button 4. Example: <i>TSYS</i>

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
BUTTON_LABEL5	Optional	Character	1	15		Label for Button 5. Example: WIPRO
BUTTON_LABEL6	Optional	Character	1	15		Label for Button 6. Example: GIRMITI
RETURN_SCREEN	Optional	Character	1	15		Return screen.
POS_RECON	Optional	Character	1	30		POS reconciliation. POS Reconciliation field to be echoed back in response to POS. Example: RetailPOS1
COUNTER	Required	Numeric	1	10		COUNTER is used for a given MAC label. Each COUNTER should be higher than the last one. This is used to authenticate the POS. Example: 100
MAC	Required	Base64 Encoded Data	•	44		Message Authentication Code. This is used to authenticate the POS. Example: fK6w3AYFSWYC7I avAjcYZUgzOCZ3 mPkRCPSYAnk31 Y=

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
MAC_LABEL	Required	Character	1	50		Associated label that tells the device which MAC_KEY to use to decrypt the value of MAC. This is used to authenticate the POS. Example: P_AFV1IM

Example

Following is an example of request packet

```

<TRANSACTION>
<FUNCTION_TYPE>DEVICE</FUNCTION_TYPE>
<COMMAND>CUST_BUTTON</COMMAND>
<DISPLAY_TEXT1>PLEASE SELECT THE COMPANY YOU HAVE WORKED IN.</DISPLAY_TEXT1>
<DISPLAY_TEXT2> YOUR CAREER</DISPLAY_TEXT2>
<DISPLAY_TEXT3>IN INDIA</DISPLAY_TEXT3>
<DISPLAY_TEXT4>.</DISPLAY_TEXT4>
<DISPLAY_TEXT5></DISPLAY_TEXT5>
<BUTTON_LABEL1>WORLD MARKETING</BUTTON_LABEL1>
<BUTTON_LABEL2>VERIFONE</BUTTON_LABEL2>
<BUTTON_LABEL3>FIRSTDATA</BUTTON_LABEL3>
<BUTTON_LABEL4>TSYS</BUTTON_LABEL4>
<BUTTON_LABEL5>WIPRO</BUTTON_LABEL5>
<BUTTON_LABEL6>GIRMITI</BUTTON_LABEL6>
</TRANSACTION>

```

Response Packet

Field	Type	Value	Description
RESPONSE_TEXT	Character		Processor response text. Example: Customer Button Captured
RESULT	Character		This indicates the Result details. Example: OK
RESULT_CODE	Numeric	Expected result code: -1, 59006, 59040	This indicates the result code. Refer to Result/Error Codes for details.

Field	Type	Value	Description
TERMINATION_STATUS	Character	SUCCESS or FAILURE	This indicates the transaction termination status. This is the overall status of the transaction irrespective of approved or declined. Like, if the output is generated then the status is SUCCESS and if no output is generated then the status will be FAILURE.
CUST_BUTTON_DATA	Character	1, 2, 3, 4, 5, 6	Represents the button selected by the user.
POS_RECON	Character		POS reconciliation field echoed back if sent in request. Example: RetailPOS1
COUNTER	Numeric		Echoes counter sent in the request. Example: 100

Example

Following is an example of response packet

```

<RESPONSE>
<RESPONSE_TEXT>Customer Button Captured</RESPONSE_TEXT>
<RESULT>OK</RESULT>
<RESULT_CODE>-1</RESULT_CODE>
<TERMINATION_STATUS>SUCCESS</TERMINATION_STATUS>
<CUST_BUTTON_DATA>5</CUST_BUTTON_DATA>
<COUNTER>1</COUNTER>
</RESPONSE>

```