

RESET_TIP

This command removes tip from a specific transaction.

Device UI Required: No

Request Packet

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
FUNCTION_TYPE	Required	Static value	N/A	N/A	PAYMENT	Type of function.
COMMAND	Required	Static value	N/A	N/A	RESET_TIP	Command name
PAYMENT_TYPE	Required	List	N/A	N/A	CREDIT DEBIT GIFT	Payment types. NOTE: PAYMENT_TYPE field is mandatory for card token based transactions.
CTROUTD	Required	Numeric	1	16		Here is the transaction ID for which Tip will be reset to zero. CTROUTD is a sequence number for PAYMENT transactions (always enabled) that is generated per Client ID. Each Client ID has its own CTROUTD sequence counter. Example: 123456

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
ENCRYPT	Conditional	Binary	N/A	N/A	TRUE FALSE	This field is required to encrypt the PAN details before passing it on to processor/gateway. In case of P2PE encryption, this field needs to be set to TRUE as value. NOTE: If this field is not present, then the application will internally treat this field as a value TRUE when the device encryption is ADE/VSD.

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
COL_3, COL_4, COL_5, COL_6, COL_7, COL_8, COL_9, COL_10	Optional	Character	1	255		<p>These fields represent Column 3 to Column 10. These fields are expected for the Merchants internal POS System, which will record any additional data and link those to the PWC CLIENT_ID and CTROUTD. When a value for COL_n is passed in, that same value will be returned in the response. These COL_n values are not indexed, or searchable in any command report. These fields are not sent to any payment processor.</p> <p>Example: Merchant defined data</p>
COUNTER	Required	Numeric	1	10		<p>COUNTER is used for a given MAC label. Each COUNTER should be higher than the last one. This is used to authenticate the POS. Example: 100</p>

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
MAC	Required	Base64 Encoded Data	N/A	N/A	N/A	Message Authentication Code. This is used to authenticate the POS.
MAC_LABEL	Required	Character	1	50		Associated label that tells the device which MAC_KEY to use to decrypt the value of MAC. This is used to authenticate the POS. Example: REG1

Example

Following is an example of request packet

```

<TRANSACTION>
<FUNCTION_TYPE>PAYMENT</FUNCTION_TYPE>
<COMMAND>RESET_TIP</COMMAND>
<COUNTER>1</COUNTER>
<MAC> ... </MAC>
<MAC_LABEL>REG2</MAC_LABEL>
<PAYMENT_TYPE>CREDIT</PAYMENT_TYPE>
<CTROUTD>5</CTROUTD>
<ENCRYPT>TRUE</ENCRYPT>
</TRANSACTION>

```

Response Packet

Field	Type	Value	Description
RESPONSE_TEXT	Character		Processor response text. NOTE: This will be implemented for future release. Example: Tip Reset.

Field	Type	Value	Description
RESULT	Character		Commonly TIP MODIFIED or DECLINED. Example: TIP MODIFIED
RESULT_CODE	Numeric	Expected result code: 6, 17	This indicates the result code.
TERMINATION_STATUS	Character	SUCCESS and FAILURE	This indicates the transaction termination status. This is the overall status of the transaction irrespective of approved or declined. Like, if the output is generated then the status is SUCCESS and if no output is generated then the status will be FAILURE.
COUNTER	Numeric		Echoes counter sent in the request. Example: 100
MERCHID	Numeric		Merchant ID. Example: 900000000123
TERMID	Numeric		Merchant ID. Example: 001
TRANS_SEQ_NUM	Numeric		Processor/Batch transaction sequence number. Example: 5
INTRN_SEQ_NUM	Numeric		PWC transaction ID. Example: 123456789
TRACE_NUM	Numeric		This field is sent from the Host Response. This field contains the Interac Sequence number from the host. Example: 140004000000004001951
TROUTD	Numeric		Transaction routing ID. Example: 123456789
CTROUTD	Numeric		CTROUTD is a sequence number for PAYMENT transactions (always enabled) that is generated per Client ID. Each Client ID has its own CTROUTD sequence counter. Example: 45

Field	Type	Value	Description
APPROVED_AMOUNT	Floating point number (decimal)		Amount approved. Example: 30.00. NOTE: This will be implemented for future release.
AUTH_REF_NUMBER	Character	Example: 123456789012345; Or, it can be empty	This tag returns in the host response with the value for the particular transaction. This is used by some merchants to refer to the transaction at the host side. Currently this is applicable only for Worldpay processor.
COL_3, COL_4, COL_5, COL_6, COL_7, COL_8, COL_9, COL_10	Character		Column 3 to Column 10 fields value will be echoed in POS response. These fields are not sent to any payment processor.
PAYMENT_MEDIA	Character		Medium of payment. Commonly VISA/MC/DISC/AMEX/DEBIT. Example: MC
PAYMENT_TYPE	Character		Payment type returned. Example: CREDIT
AUTH_CODE	Character		Processor authorization number. Example: 123123.
RECEIPT_DATA	Character		Receipt Data.
TRANS_DATE	Character		Transaction date returned. Example: 2016.09.20
TRANS_TIME	Character		Transaction time returned. Example: 09:16:25

Example

Following is an example of response packet

```
<RESPONSE>
<AUTH_CODE>090435</AUTH_CODE>
<CTROUTD>5</CTROUTD>
<INTRN_SEQ_NUM>50408</INTRN_SEQ_NUM>
<PAYMENT_TYPE>CREDIT</PAYMENT_TYPE>
<RESULT>TIP MODIFIED </RESULT>
<RESULT_CODE>17</RESULT_CODE>
<TERMINATION_STATUS>SUCCESS</TERMINATION_STATUS>
<TROUTD>859</TROUTD>
</RESPONSE>
```