

Dynamic Currency Conversion (DCC)

Dynamic Currency Conversion (DCC) allows a non-domestic cardholder, while travelling, to have a choice to pay in their home currency instead or the base currency used by the merchant. This may provide a better rate than their credit card provider, at times.

The PropertiesData.xml file contains all parameters necessary to configure the payment device with DCC. Refer to DCC Parameters for more details on DCC parameters.

HFEX.DAT configuration file contains different BINs for foreign or international cards. SCA does BIN look up in HFEX.DAT file before performing the card rate request. If matching BIN is not found, then SCA will skip DCC query to Fexco host. This file is present under /mnt/flash/userdata/usr1 location. During start up this file is read and stored in the memory to reduce the look up time during the transaction. If this file is not found in the user flash, then SCA application will assume that the file is not present in this solution and proceeds to Fexco integration without doing the BIN look up. The application will use the currency details that are sent by Fexco.

SCA application also approve DCC transactions offline if it meets the SAF eligibility criteria based on USD amount. The transaction will be processed online in DCC using the rate and currency selected by the cardholder at the time when transaction was stored offline. This scenario would be coming into play if device has got DCC rate through an acquirer, however, loses connectivity to the gateway while processing the DCC selection of cardholder. This feature can be controlled by ALLOWDCCTOSAF parameter. Disabling this parameter would result in approving the transactions in Local Currency.

Example DCC Screen

DCC selection screen is added as part of the transaction flow after card data validation for the user to select the home currency, if the transaction is eligible for DCC.



DCC Controller



DCC Controller is added to handle initializing and DCC processing as part of the payment flow. This controller performs all required actions to check the DCC eligibility for the current transaction and update command object with the currency details. This controller provides the following two services:

Fields	Description
initDCC	This service is used to initialize and perform all actions, needed for DCC processing. For Fexco DCC Host, it checks for the presence of HFEX.DAT and loads them into memory. Bitmaps are used to load the data of HFEX.DAT data into memory.
DCCProcessing	This service is used to check the DCC eligibility for the given transaction and prompts the user for currency selection. For Fexco DCC Host, it does BIN look up into HFEX.DAT file, if this is successful, then it does the card rate request with the Fexco host.

Following are the fields description which are sent in host request to PWC if transaction is eligible for DCC. These fields are added to CAPTURE and REFUND sections of HostMessages.xml file.

Field Name	Rules	Data Types	Length	Description
DCC_IND	Required for DCC transaction	Integer	1	DCC Indicator. Valid values: 1 - Transaction is DCC eligible and cardholder has accepted the option. 2 - Transaction is not eligible for DCC. 3 - Transaction is DCC eligible yet cardholder has not accepted the option.



Field Name	Rules	Data Types	Length	Description
DCC_TRAN_AMOUNT	Conditional	VARCHAR	Length 16	The transaction amount provided by SCA that has been calculated in the currency requested by the Cardholder. • Device will be responsible for sending all amounts with or without decimals to PWC, based on the requirem ents of the currency code. • PWC will only be required to explicitly remove the decimal when sending transaction to FDRC. • If DCC_TRA N_AMOU NT is provided, FDRC
				Requires DCC_CUF R_CODE
				and
		https://verifone.clou	ıd/docs/sca-functional-	specification/html/featacesout
				Updated: 23 Jan 20 to also be
				provided
				• DCC_TRA
				N_AMOU
				NT



Field Name	Rules	Data Types	Length	Description
DCC_CONV_RATE	Conditional	Decimal	7	The DCC Conversion Rate provided by SCA that was used in calculating the DCC_TRAN_AMOUNT. • DCC_CON V_RATE is required for DCC_IND =1. • FDRC Requires DCC_CON V_RATE to be provided any time DCC_TRAN_AMOUNT is provided.
DCC_CURR_CODE	Required for DCC transaction	Integer	3	The DCC Currency Code used for DCC Calculations. This value will be standardized across all Countries. FDRC Requires DCC_CURR_CODE to be provided on all DCC Attempts including DCC_IND 1,2,3.



Field Name	Rules	Data Types	Length	Description
DCC_DATETIME	Conditional	DateTime	20	This indicates the date and time, when the DCC conversion took place. This is a PWC requirement as the DCC calculation will occur prior to the transaction being sent to PWC. This is used as an Audit Trail. This value will be provided by SCA/Merchants Integration.



Field Name	Rules	Data Types	Length	Description
DCC_TIMEZONE	Conditional	Integer	3	This is the time zone for the DCC_DATETIME that will be provided by SCA/Merchants Integration. • FDRC requires DCC_TIMEZONE field to be provided then this must be sent as +- and 2 digit how offset from GMT. • If DCC_TIMEZONE in the provided that the provided by SCA, then PW will default the merchants so the provided that the provided that the merchants so the provided that the merchants so the provided that the merchants so the provided that the provid



Field Name	Rules	Data Types	Length	Description
DCC_SOURCE	Conditional	Integer	1	The source of the DCC Rates will be provided as an Audit Trail for PWC: 0 - Merchant Supplied Values 1 - Device-FEXCO Direct 2 - PWC xxxx (Reserved for Future Use) and so on.
DCC_CALCULATION	Conditional	Integer	1	The source of the calculation of DCC_TRAN_AMOUNT. This will be used in as an Audit Trail for PWC: 0 - Merchant Supplied Values 1 - PWC performs calculation based on DCC_CONV_RATE provided by Merchant 2 - Reserved for future use

Example DCC Receipt



https://verifone.cloud/docs/sca-functional-specification/html/features/dcc