

## SdiLanguage Class Reference

```
#include <sdi_lang.h>
```

### Public Member Functions

|          |                                                                              |
|----------|------------------------------------------------------------------------------|
|          | <a href="#">SdiLanguage</a> ()                                               |
|          | <a href="#">SdiLanguage</a> (Language languageId)                            |
| Language | <a href="#">getLanguageId</a> ()                                             |
| void     | <a href="#">setLanguageId</a> (Language languageId)                          |
| void     | <a href="#">selectLanguage</a> (unsigned char *rsp, unsigned short *rspSize) |

### Constructor & Destructor Documentation

#### [?](#) SdiLanguage() [1/2]

[SdiLanguage](#) ( )

default constructor

#### [?](#) SdiLanguage() [2/2]

[SdiLanguage](#) ( Language *languageId* ) explicit

constructor with predefined language id

Parameters

languageId preset of language id

### Member Function Documentation

## ? getLanguageId()

Language getLanguageId ( )

get language id

Returns

language id

## ? selectLanguage()

```
void selectLanguage ( unsigned char *  rsp,  
                    unsigned short * rspSize  
                    )
```

select language from response

Parameters

*rsp* response

*rspSize* size of response

## ? setLanguageId()

```
void setLanguageId ( Language languageId )
```

set language id

Parameters

*languageId* language id to set

---

The documentation for this class was generated from the following files:

- sdi/src/[sdi\\_lang.h](#)
- sdi/src/[sdi\\_lang.cpp](#)