







REACTIVATE

This command reactivates a Gift or Merchandise Credit card with an initial (non-zero) balance.

Device UI Required

Display	User Action	Terminal Action
<div><div>01:21</div><div>Reactivation</div><div><div>VISA</div><div></div><div></div><div></div><div></div><div></div></div><div><div>Total</div><div>USD \$ 100.00</div><div>Cancel</div></div><div>Swipe Card</div></div>	Use the card for performing a gift card reactivation.	The device displays card entry screen.
<div><div>06:00</div><div>Authorizing</div><div></div></div>	No action	The device displays authorizing screen for reactivation.

Request Packet

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
FUNCTION_TYPE	Required	Static value	N/A	N/A	PAYMENT	Type of function
COMMAND	Required	Static value	N/A	N/A	REACTIVATE	Command name
PAYMENT_TYPE	Optional	List	N/A	N/A	GIFT MERCH_CREDIT	Payment type for Merchandise Credit. PAYMENT_TYPE is mandatory for credit transactions.
PAYMENT_SUBTYPE	Optional	List	N/A	N/A		Payment subtype. BLACKHAWK
TRANS_AMOUNT	Required	Floating point number (decimal)	1(2)	6(2)		This indicates the amount. This amount can be a zero amount. Example
MANUAL_ENTRY	Optional	Boolean	N/A	N/A	TRUE FALSE	This is to instruct the account information keypad on the device.
MANUAL_PROMPT_OPTIONS	Optional	Character	1	50	NOEXP	This field is applicable to MANUAL_ENTRY. TRUE. The value is used when this field is not prompt for entry.
TOT_NUM_CARDS	Optional	Numeric	1	2	EX: 10	Total number of cards to activate. Example
ENCRYPT	Conditional	Boolean	N/A	N/A	TRUE FALSE	This field is required for PAN details before processor/gateway encryption, this field is set to TRUE as default. If this field is not present, the application will treat this field as a value for device encryption.
POS_RECON	Optional	Character	1	30		POS reconciliation file. Reconciliation file back in response to RetailPOS1
CARD_TOKEN	Conditional	Character	1	40		Card token is provided by the gateway-based application as a unique card. Refer to the Token section. Example: 7987654321098

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
CASHIER_ID	Optional	Character	1	10		This indicates the cashier performing the transaction. Example: 7987
COL_3, COL_4, COL_5, COL_6, COL_7, COL_8, COL_9, COL_10	Optional	Character	1	225		These fields represent additional data added to Column 10. The data is for the Merchant System, which will contain additional data added to PWC CLIENT_TRANSACTION. When a value for COL_3 is in, that same value will be in the response. These fields are not indexed, so the command report will not be sent to any payment processor. Example: Merchant System Data
BANK_USERDATA	Conditional	Character	1	50		Returned with CASHIER_ID. Whatever comes in the BANK_USERDATA field for the token should be returned in the response. Example: Merchant System Data
CDD_DATA	Optional	Character	1	30		Customer Defined Data through field and host request if the POS request is in the POS response. Example: CDD_DATA>IN CDD_DATA>IN CDD_DATA>
CAPTURECARD_EARLYRETURN	Optional	Binary			<ul style="list-style-type: none"> • TRUE • FALSE 	If the sending value is TRUE, the application must send the POS before processing the card checking in place of the card or masked PAN. If the value is FALSE, SCA will cache the card but will only use the card for subsequent CAPTURECARD requests containing explicit card data. If it will discard.
EMV_TAGS_REQD	Character	Binary			Valid values: Y/N	EMV tags detail if the card is sent in request. If the tags in the response are CAPTURECARD, the card is sent as TRUE.

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
INVOICE	Required	Character	1	40		Merchant invoice number. This field is used for the 40 characters (A-Z, 0-9, and special characters). These are not case sensitive. INVOICE. NOT used with the application. maximum invoice number host used in the application. allows numeric values. not be all zeroes.
LANE	Optional	Numeric	1	8		This field is used for the lane. Example: 1
PURCHASE_ID	Conditional	Character	1	25		Purchase ID. This field is used for Level II processing. Customer Code. characters are stored in PURCHASE_ID.
SERVER_ID	Optional	Numeric	1	10		This indicates the server performing the transaction. Example: 560
SHIFT_ID	Optional	Character	1	1		This indicates the shift. Example: 2
STORE_NUM	Optional	Character	1	6		Store number. Example: 1
TABLE_NUM	Optional	Numeric	1	5		Table number. Example: 10
TRAINING_MODE	Optional	List	1	3	OFF ON	This field is included in the Training Mode. Transactions are not processed for host simulation. mocked for application. DEMO parameter. transactions will be processed. Training Mode. pass <TRAINING_MODE> TRAINING_MODE. COUNTER is used for label. Each COUNTER higher than the previous to authenticate transaction. 100
COUNTER	Required	Numeric	1	10		
MAC	Required	Base64 Encoded Data	N/A	N/A	N/A	Message Authentication Code is used to authenticate transaction.

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
MAC_LABEL	Required	Character	1	50		Associated label which MAC_KEY the value of MAC_KEY authenticate the REG1

Keyed Account Information

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
ACCT_NUM	Optional	Numeric	1	25	PAYMENT	This field is used to enter the account number manually. For this MANUAL_ENTRY must be set to TRUE. Pre-swipe data will not be honored. Example: 67823456781313
CARD_EXP_MONTH	Required	Numeric	2	2		Card expiry month. NOTE: If the encryption is set to TRUE, then SCI will use 12 as default value if this field is not passed. Example: 12
CARD_EXP_YEAR	Required	Numeric	2	2		Card expiry year. NOTE: If encryption is set to TRUE, SCI will use 49 as default value if this field is not passed. Example: 49
BARCODE	Optional	Character	1	100		Barcode scanning option.
PIN_CODE	Required	Numeric	1	12		Gift PIN code. Example: 5.00
CVV2	Optional	Numeric	1	10		Card Verification Value 2.

Example

Following is an example of request packet

```
<TRANSACTION>
  <FUNCTION_TYPE>PAYMENT</FUNCTION_TYPE>
  <COMMAND>REACTIVATE</COMMAND>
  <COUNTER>1</COUNTER>
  <MAC> ... </MAC>
  <MAC_LABEL>REG2</MAC_LABEL>
  <PAYMENT_TYPE>GIFT</PAYMENT_TYPE>
  <PAYMENT_SUBTYPE>BLACKHAWK</PAYMENT_SUBTYPE>
  <BARCODE>88590991979</BARCODE>
  <TRANS_AMOUNT>100.00</TRANS_AMOUNT>
  <TOT_NUM_CARDS>10</TOT_NUM_CARDS>
</TRANSACTION>
```

Field	Type	Value	Description
RESPONSE_TEXT	Character		Processor response text. Example: CAPTURED.
RESULT	Character		This indicates the Result details. Commonly CAPTURED or DECLINED.
RESULT_CODE	Numeric	Expected result code: 4, 59040	This indicates the result code.
TERMINATION_STATUS	Character	SUCCESS and FAILURE	This indicates the transaction termination status. This is the overall status of the transaction irrespective of approved or declined. Like, if the output is generated then the status is SUCCESS and if no output is generated then the status will be FAILURE.
POS_RECON	Character		POS reconciliation field echoed back if sent in request. Example: RetailPOS1
COUNTER	Numeric		Echoes counter sent in the request. Example: 100
COMMAND	Character		Echoes the command name, sent in the request.
BATCH_TRACE_ID	Character		Batch Trace ID, returned from PWC. This is conditional field. Example: 12cc7b17-4b45-4344-b412-5432
EMBOSSSED_ACCT_NUM	Numeric		Card number conditionally returned if present in the SSI response. Returned if payment type = GIFT and returnembossednumforgift is enabled. Example: 6499991111115789
HOST_RESPCODE	Numeric		This field will be sent if present in the host response. Example: 000
TRANS_SEQ_NUM	Numeric		Processor/Batch transaction sequence number. NOTE: For Private Label transaction (ADS), PT_SEQ_NUM field will be mapped to TRANS_SEQ_NUM and TROUTD fields back to SCA. Example: 5
INTRN_SEQ_NUM	Numeric		PWC transaction ID. Example: 123456789
MERCHID	Numeric		Merchant ID. Example: 9000000000123
TERMID	Numeric		Merchant ID. Example: 001
AUTH_CODE	Character		Processor authorization number. Example: 123456
TROUTD	Numeric		Transaction routing ID. Example: 123456789

Field	Type	Value	Description
CTROUTD	Numeric		CTROUTD is a sequence number for PAYMENT transactions (always enabled) that is generated per Client ID. Each Client ID has its own CTROUTD sequence counter. Example: 45 NOTE: For Private Label transaction (ADS), PT_CTROUTD field will be mapped to CTROUTD field back to SCA.
LPTOKEN	Numeric		LP Token is a non-sensitive unique number assigned to each unique card number processed with the UGP gateway. This value will automatically increment by one for each unique card number. This is a conditional field. NOTE: Refer to Responses from Point section in Message Format. Example: 12457
PAYMENT_MEDIA	Character		Mode of payment. Commonly VISA/MC/DISC/AMEX/DEBIT. Example: : GIFT/MERCHANDISE
PAYMENT_TYPE	Character		Payment type returned, like Gift. Example: GIFT/MERCH_CREDIT
ACCT_NUM	Numeric		Returned the masked account number. NOTE: If UNMASKEDPANFORNONPCI=1 then the account number will be sent back to POS as unmasked for non PCI cards. Refer to GSC Parameters for more details on the parameter. Example: 600649*****9147
CARDHOLDER	Character		Returned for swiped transactions. Example: TEST PROCESSOR
CARD_EXP_MONTH	Numeric		Card expiry month. Example: 12
CARD_EXP_YEAR	Numeric		Card expiry year. Example: 20
CARD_ENTRY_MODE	Character		Returns card entry mode values. NOTE: Refer to Card Entry Mode for details on possible values. Example: 123123
EMV_TAGS	Character		This is returned for Early Card Capture payment flows for Non PCI BIN ranges, only when EMV_TAGS_REQD is sent as Y.
CARD_CLASS	Numeric		This field is returned to identify the card type of the gift transaction. Example: 0
PIN_CODE	Numeric		Gift PIN code. This is a conditional field. This field will return in POS response if GIFTPINTOPOS parameter is enabled. Refer to Application Parameters for more details on the parameter.

Field	Type	Value	Description
APPROVED_AMOUNT	Floating point number		The amount which got approved. Example: 5.00.
AVAILABLE_BALANCE	Floating point number		Available balance on the card used for transaction. This field will be returned to POS, when the Host returns the Available Balance data. SCA application sends <BALANCE_ENQ> as Host request field and based on the processor, it returns the Available Balance, and SCA will send it back to POS. Example: 100.00.
PREVIOUS_BALANCE	Floating point number		Previous balance on card. Example: 200.00.
RECEIPT_DATA	Character		Receipt Data.
TRANS_DATE	Character		Transaction date returned. Example: 2016.09.20
TRANS_TIME	Character		Transaction time returned. Example: 09:16:25
TOT_NUM_CARDS	Numeric		Total number of cards activated. Example: 1-99
VSP_CODE	Numeric		If present, returns the VSP code. Example: 100
VSP_RESULTDESC	Boolean	SUCCESS or FAILURE	If present, returns the VSP result description.
VSP_TRXID	Numeric		If present, returns the VSP transaction ID. Example: 012345678901234567
TRAN_LANG_CODE	Character	en – English fr – French es – Spanish	This field contains the language code for the current transaction which is finalized based on the configured language on terminal and language preference from the card. This field will be returned only whenever the Card data is captured from cardholder during transaction flow. If Language code is not available from card, then terminal language will be returned. This field needs to be added for the below transaction flows.
AUTH_REF_NUMBER	Character	Example: 123456789012345 Or It can be empty	This tag returns in the host response with the value for the particular transaction. This is used by some merchants to refer to the transaction at the host side. Currently this is applicable only for Worldpay processor.
COL_3, COL_4, COL_5, COL_6, COL_7, COL_8, COL_9, COL_10	Character		Column 3 to Column 10 fields value will be echoed in POS response. These fields are not sent to any payment processor.

Processor-Based Token (Conditional)

Note

For use with host based processors supporting card based token implementations.

Field	Type	Value	Description
CARD_TOKEN	Character		Card Token field is returned in most of the GIFT administrative transactions. Example: 7987654321098765 NOTE: Refer to Card Tokens section in Point Integration Best Practices.
TOKEN_SOURCE	Character		Source of the token. Example: PWC

Transaction Performance Metric

Note

These fields are returned, if SCAPERFMETRIC parameter ([Application Parameters](#)) is enabled.

Field	Type	Value	Description
UI_TIME	Time		This indicates the time duration, for which the device screen is displayed (like error message, prompt screen, remove card screen) till any user action is performed in the command execution flow. This field is not applicable to capture the time for the Processing, Authorizing and transaction status screen. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <UI_TIME>44.028</UI_TIME>
HOST_TIME	Time		This indicates the time taken for the Connection to the host, sending request and receives data from the host. This field also take the cumulative time for multiple requests which may sent to the host during the transaction including two legged transactions, timeout requests, Auto Last Tran requests, DCC, Credit app proxy. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <HOST_TIME>1.389</HOST_TIME>
CMD_TIME	Time		This field indicates the total amount of time for a command, which is executed by the application from request received to the response sent. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <CMD_TIME>70.765</CMD_TIME>

Example

Following is an example of response packet

<RESPONSE>
 <APPROVED_AMOUNT>100.00</APPROVED_AMOUNT>
 <AVAILABLE_BALANCE>100.00</AVAILABLE_BALANCE>
 <ACCT_NUM>600649*****9147</ACCT_NUM>
 <AUTH_CODE>ABC001</AUTH_CODE>
 <CARDHOLDER>PROCESSOR/GIFT</CARDHOLDER>
 <CTROUTD>141</CTROUTD>
 <INTRN_SEQ_NUM>569230</INTRN_SEQ_NUM>
 <PAYMENT_MEDIA>GIFT</PAYMENT_MEDIA>
 <PAYMENT_TYPE>GIFT</PAYMENT_TYPE>
 <RESPONSE_TEXT>CAPTURED</RESPONSE_TEXT>
 <RESULT>CAPTURED</RESULT>
 <RESULT_CODE>4</RESULT_CODE>
 <TERMINATION_STATUS>SUCCESS</TERMINATION_STATUS>
 <TRANS_SEQ_NUM>19</TRANS_SEQ_NUM>
 <TROUTD>569230</TROUTD>
 <TRAN_LANG_CODE>en</TRAN_LANG_CODE>
</RESPONSE>