



https://verifone.cloud/docs/sca-functional-specification/protocol_spec/reports/dailysummary_presettlement

Updated: 20-May-2025

DAILY SUMMARY/PRE-SETTLEMENT

Daily Summary

The Daily Summary report returns a summary report for each Point command type (sale, credit, post-auth, etc.) for the Client ID. The Daily Summary report requires COMMAND as a <RESPONSEFIELDS/> tag to return results for each transaction type. (Leaving this tag out will not cause the transaction to fail the validation; however, it will not return information for the transaction types.) Sending optional parameters with the command request, such as start and end date, starting and ending time, and amount range, will limit the report's results as desired. The Daily Summary Report returns output requested in the <RESPONSEFIELDS/> tag.

Pre-Settlement

The Pre-Settlement report returns summary information on the transactions that have been approved since the current batch was opened. The Pre-Settlement report requires COMMAND as a <RESPONSEFIELDS/> tag to return results for each transaction type. (Leaving this tag out will not cause the transaction to fail the validation; however, it will not return information for the transaction types). Sending optional parameters with the command request, such as start and end date, starting and ending time, and amount range, will limit the report's results as desired. The Pre-Settlement report returns output requested in the <RESPONSEFIELDS/> tag.

Device UI Required: No

Request Packet

Field	Rule	Type	Minimum	Maximum	Value(s)	Descript
FUNCTION_TYPE	Required	Static value	N/A	N/A	REPORT	Type of func
COMMAND	Required	Static value	N/A	N/A	DAYSUMMARY or PRESETTLEMENT	Command n
MAX_NUM_RECORDS_RETURNED	Required	Numeric	1	4	Maximum valid value: 8000	Maximum n of records re
SEARCHFIELDS	Required	List	N/A	N/A	See SEARCHFIELDS section for child elements.	List of fields required to s search.

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
COL_3, COL_4, COL_5, COL_6, COL_7, COL_8, COL_9, COL_10	Optional	Character 1		255		These fields represent Columns 3 to Column 10. These fields are expected for the Mercantile internal POS System, which does not record any additional data. These fields link those to the PWC CLIENT and CTROUTD. When a value for COL_n is passed that same value will be returned in response. The COL_n values are not indexed, not searchable in command response. These fields are sent to any processor. Example: MERCHANT defined data. Choose from the following: NOTE: COMMAND, TRANS_AMOUNT, TROUTD, and TROUTD are required for DAYSUMMARY and PRESETTLEMENT report. POS reconciliation. POS Reconciliation field to be echoed back in response. POS. Example: RetailPOS1
RESPONSEFIELDS	Required	List			Valid Values: COMMAND, TRANS_AMOUNT, TROUTD, PAYMENT_TYPE, CTROUTD, CASHBACK_AMNT, and TIP_AMOUNT	
POS_RECON	Optional	Character 1		30		

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
COUNTER	Required	Numeric	1	10		COUNTER for a given Message label. Each COUNTER be higher than the last one. This is used to authenticate POS. Example: REG1
MAC	Required	Base64 Encoded Data	N/A	N/A		Message Authentication Code. This is used to authenticate POS.
MAC_LABEL	Required	Character	1	50		Associated label tells the device which MAC to use to decode value of MAC is used to authenticate POS. Example: REG1

SEARCHFIELDS child elements

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
START_TRANS_DATE	Conditional	Date				Transaction start date. This is a recommended field. Example: 2016.03.23
START_TRANS_TIME	Conditional	Time				Transaction start time. Example: 15:30:00
END_TRANS_DATE	Optional	Date				Defaults to START_TRANS_DATE. Example: 2016.03.24
END_TRANS_TIME	Optional	Time				Defaults to START_TRANS_TIME. Example: 15:30:01
PAYMENT_TYPE	Conditional	List	N/A	N/A		Payment type used in the transaction. Example: CREDIT
REQUEST_COMMAND	Conditional	List	N/A	N/A		The command requested for transaction. Example: SALE

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
ACCT_NUM	Conditional	Numeric	1	16		The card number used in the transaction. The card number passed MUST be in a masked format, only the first six and the last four digits of the number can be passed - this is how Point platform pulls the cards on the reports. The length of the ACCT_NUM must equal 16 bytes. For card numbers fewer than 16 digits, add extra "*" between the first 6 and the last 4 digits. Example: 400555*****0019
INVOICE	Conditional	Character	1	6		Merchant invoice number. Example: ASD156
BATCH_SEQ_NUM	Conditional	Numeric	1			Sequence number of the batch. Example: 23
START_TRANS_AMOUNT	Conditional	Floating point number	1(2)	6(2)		Transaction start amount. Example: 0.00
END_TRANS_AMOUNT	Conditional	Floating point number	1(2)	6(2)		Transaction end amount. Example: 50.00
START_TROUTD	Conditional	Numeric	1	10		Transaction routing ID starts with. Example: 50
END_TROUTD	Optional	Numeric	1	10		Defaults to START_TROUTD. Example: 100
STATUS_CODE	Conditional	Numeric	1	10		Transaction status code. Example: 4

Example

Following is an example of request packet

```

<TRANSACTION>
  <COUNTER>1</COUNTER>
  <MAC> ... </MAC>
  <MAC_LABEL>REG2</MAC_LABEL>
  <FUNCTION_TYPE>REPORT</FUNCTION_TYPE>
  <COMMAND>DAYSUMMARY</COMMAND>

```

```

<MAX_NUM_RECORDS_RETURNED>200</MAX_NUM_RECORDS_RETURNED>
<RESPONSEFIELDS>
<COMMAND/>
<TRANS_AMOUNT/>
<TROUTD/>
<CASHBACK_AMNT/>
<TIP_AMOUNT/>
</RESPONSEFIELDS>
<SEARCHFIELDS>
<START_TRANS_DATE>2016.01.01</START_TRANS_DATE>
<END_TRANS_DATE>2016.05.31</END_TRANS_DATE>
</SEARCHFIELDS>
</TRANSACTION>

```

Response Packet

Field	Type	Value	Description
CLIENT_ID	Numeric		CLIENT_ID is the combination an ACCOUNT number, a SITE number, and a TERMINAL number in that order. Example: 100010001
RETURN_FLD_HDRS	Numeric		Returns field headers. Example: 0
FORMAT	Conditional	xml	Format of the command.
SERIAL_NUM	Character		Serial number. Example: 123456789
DEVICEKEY	Character		Device key.
MAX_NUM_RECORDS_RETURNED	Numeric		Maximum number of records returned. Example: 800
DELIMITER	Static Value	,	Delimiter to enter multiple entry in a field.
FUNCTION_TYPE	Static Value	REPORT	Function type
DEVTYPE	Character		Device type
NUM_RECORDS_FOUND	Numeric		Number of records found. Example: 167
START_TRANS_DATE, END_TRANS_DATE, START_TRANS_TIME, END_TRANS_TIME, PAYMENT_TYPE, REQUEST_COMMAND, ACCT_NUM, INVOICE, BATCH_SEQ_NUM, START_TRANS_AMOUNT, END_TRANS_AMOUNT, START_TROUTD, END_TROUTD, STATUS_CODE			These fields and their values from the SEARCHFIELDS parameter of the request will be included in the response so the integrator will know the criteria upon which the report is based.

Field	Type	Value	Description
COMMAND, SALE_AMOUNT, TROUTD, PAYMENT_TYPE, CASHBACK_AMNT, TIP_AMOUNT, CTROUTD			These fields will return for each record if they are specified in the RESPONSEFIELDS parameter of the request. NOTE: TRANS_AMOUNT returns as SALE_AMOUNT.
CHARGE_TOTAL, ITEMCOUNT			These fields will also be included for each record.
COL_3, COL_4, COL_5, COL_6, COL_7, COL_8, COL_9, COL_10	Character		Column 3 to Column 10 fields value will be echoed in POS response. These fields are not sent to any payment processor.
POS_RECON	Character		POS reconciliation field echoed back if sent in request. Example: RetailPOS1

Transaction Performance Metric

Note

These fields are returned, if SCAPERFMETRIC parameter ([Application Parameters](#)) is enabled.

Field	Type	Value	Description
UI_TIME	Time		This indicates the time duration, for which the device screen is displayed (like error message, prompt screen, remove card screen) till any user action is performed in the command execution flow. This field is not applicable to capture the time for the Processing, Authorizing and transaction status screen. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <UI_TIME>44.028</UI_TIME>
HOST_TIME	Time		This indicates the time taken for the Connection to the host, sending request and receives data from the host. This field also take the cumulative time for multiple requests which may sent to the host during the transaction including two legged transactions, timeout requests, Auto Last Tran requests, DCC, Credit app proxy. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <HOST_TIME>1.389</HOST_TIME>
CMD_TIME	Time		This field indicates the total amount of time for a command, which is executed by the application from request received to the response sent. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <CMD_TIME>70.765</CMD_TIME>

Example

Following is an example of response packet

```
<RESPONSE>
  <ACCOUNT>1</ACCOUNT>
  <SITE>0001</SITE>
  <TERM>0001</TERM>
  <DEVTYPE>VX805</DEVTYPE>
  <RETURN_FLD_HDRS>0</RETURN_FLD_HDRS>
  <FORMAT>xml</FORMAT>
  <SERIAL_NUM>1234565789</SERIAL_NUM>
  <DEVICEKEY>*****</DEVICEKEY>
  <MAX_NUM_RECORDS_RETURNED>200</MAX_NUM_RECORDS_RETURNED>
  <FUNCTION_TYPE>REPORT</FUNCTION_TYPE>
  <DELIMITER />
  <NUM_RECORDS_FOUND>167</NUM_RECORDS_FOUND>
  <SEARCHFIELDS>
    <START_TRANS_DATE>2016.01.01</START_TRANS_DATE>
    <END_TRANS_DATE>2016.05.31</END_TRANS_DATE>
  </SEARCHFIELDS>
  <RECORDS>
    <RECORD>
      <COMMAND>SALE</COMMAND>
      <ITEMCOUNT>56</ITEMCOUNT>
      <SALE_AMOUNT>56.00</SALE_AMOUNT>
      <TIP_AMOUNT>.00</TIP_AMOUNT>
      <CASHBACK_AMNT>.00</CASHBACK_AMNT>
      <CHARGE_TOTAL>56.00</CHARGE_TOTAL>
    </RECORD>
    <RECORD>
      <COMMAND>CREDIT</COMMAND>
      <ITEMCOUNT>1</ITEMCOUNT>
      <SALE_AMOUNT>1.00</SALE_AMOUNT>
      <TIP_AMOUNT>.00</TIP_AMOUNT>
      <CASHBACK_AMNT>.00</CASHBACK_AMNT>
      <CHARGE_TOTAL>1.00</CHARGE_TOTAL>
    </RECORD>
    <RECORD>
      <COMMAND>PRE_AUTH</COMMAND>
      <ITEMCOUNT>8</ITEMCOUNT>
      <SALE_AMOUNT>8.00</SALE_AMOUNT>
      <TIP_AMOUNT>.00</TIP_AMOUNT>
      <CASHBACK_AMNT>.00</CASHBACK_AMNT>
      <CHARGE_TOTAL>8.00</CHARGE_TOTAL>
    </RECORD>
    <RECORD>
      <COMMAND>POST_AUTH</COMMAND>
      <ITEMCOUNT>7</ITEMCOUNT>
      <SALE_AMOUNT>7.00</SALE_AMOUNT>
      <TIP_AMOUNT>.00</TIP_AMOUNT>
      <CASHBACK_AMNT>.00</CASHBACK_AMNT>
      <CHARGE_TOTAL>7.00</CHARGE_TOTAL>
    </RECORD>
    <RECORD>
```

```
        <COMMAND>VOID</COMMAND>
        <ITEMCOUNT>1</ITEMCOUNT>
        <SALE_AMOUNT>1.00</SALE_AMOUNT>
        <TIP_AMOUNT>.00</TIP_AMOUNT>
        <CASHBACK_AMNT>.00</CASHBACK_AMNT>
        <CHARGE_TOTAL>.00</CHARGE_TOTAL>
    </RECORD>
</RECORDS>
</RESPONSE>
```