

https://verifone.cloud/docs/sca-functional-specification/device_transaction/parameters_query

Updated: 23-Sep-2025

Parameters Query

This command allows the POS to retrieve SCA parameter values from the payment device (TranslateConfig.xml).

Rules

The GET_PARM command is intended for non-payment purposes and is to be used outside of a payment transaction.

Configuration Parameters

There is no configuration parameter associated wih this command functionality.

GET_PARM (Message Interface)

The following tables provide detailed protocol information, including field descriptions and examples.

Device UI Required: No

Request Packet

Note

Neo device (M450) is being used to capture screenshots for the Device UI Requirement section.

Field	Rule	Type	Minimun	n Maximum	Value(s)	Description
FUNCTION_TYP	E Required $\frac{S}{v}$	tatic alue	N/A	N/A	DEVICE	Type of function
COMMAND	Required S	tatic alue	N/A	N/A	GET_PARM	I Command name

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
PARAM	Required	Character	1			Pipe-delimited list of parameters to retrieve specified by POS. Only listed parameters will appear in the response. Refer Vantiv Direct or Engage Parameters guide, Config.sys or config.usrl name column for parameter names. Example: IPPAH IPPAP, MID
POS_RECON	Optional	Character	1	30		POS reconciliation. POS Reconciliation field to be echoed back in response to POS. Example: RetailPOS1
COUNTER	Required	Numeric	1	10		COUNTER is used for a given MAC label. Each COUNTER should be higher than the last one. This is sed to authenticate the POS. Example: 100
MAC	Required	Base64 Encoded Data	N/A	N/A	N/A	Message Authentication Code. This is used to authenticate the POS.
MAC_LABEL	Required	Character	1	50		Associated label that tells the device which MAC_KEY to use to decrypt the value of MAC. This is used to authenticate the POS. Example: REG1

Example

Following is an example of request packet

Response Packet

Field	Type	Value	Description
RESPONSE_TEXT	Character		Processor response text. Example: Operation SUCCESSFUL

Field	Type	Value	Description
RESULT	Character		This indicates the Result details. Example: OK
RESULT_CODE	Numeric	Expected result code: -1, 59001, 59006, 59040	This indicates the result code. Refer to Result/Error Codes for details.
TERMINATION_STATUS	Character	SUCCESS or FAILURE	This indicates the transaction termination status. This is the overall status of the transaction irrespective of approved or declined. Like, if the output is generated then the status is SUCCESS and if no output is generated then the status will be FAILURE.
PARAM	Character		Returns the list of parameters. Example: IPPAH=certssl.protectedtransactions.com IPPAP=443
POS_RECON	Numeric		POS reconciliation field echoed back if sent in request. Example: RetailPOS1
COUNTER	Numeric		Echoes counter sent in the request. Example: 100

Transaction Performance Metric

Note

These fields are returned, if SCAPERFMETRIC parameter (<u>Application Parameters</u>) is enabled.

Field	Type Value	Description
UI_TIME	Time	This indicates the time duration, for which the device screen is displayed (like error message, prompt screen, remove card screen) till any user action is performed in the command execution flow. This field is not applicable to capture the time for the Processing, Authorizing and transaction status screen. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <ui_time>44.028</ui_time>
HOST_TIME	E Time	This indicates the time taken for the Connection to the host, sending request and receives data from the host. This field also take the cumulative time for multiple requests which may sent to the host during the transaction including two legged transactions, timeout requests, Auto Last Tran requests, DCC, Credit app proxy. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <pre></pre>
CMD_TIME	Time	This field indicates the total amount of time for a command, which is executed by the application from request received to the response sent. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <cmd_time>70.765</cmd_time>

Example

Following is an example of response packet