



https://verifone.cloud/docs/sca-functional-specification/device_transaction/email_capture

Updated: 23-Sep-2025

Email Capture

This command directs the device to capture an email address from a customer.

Rules

1. The EMAIL command is intended for non-payment purposes and is to be used outside of a payment transaction.
2. This command is supported by Engage devices only.

Configuration Parameters

There is no configuration parameter associated with this command functionality.

EMAIL (Message Interface)

The following tables provide corresponding device UI interactions, detailed protocol information, including field descriptions and examples.

Device UI Required

Note

Neo device (M450) is being used to capture screenshots for the Device UI Requirements section.

Display

User Action

Terminal Action



Enter the email address.

The device displays the email address entry screen.

Request Packet

Field	Rule	Type	Minimum	Maximum	Value(s)	Description
FUNCTION_TYPE	Required	Static value	N/A	N/A	PAYMENT	Type of function
COMMAND	Required	Static value	N/A	N/A	EMAIL	Command name
EMAILDATA	Optional	Character		257		This field is for email data. This can be sent to pre-populate email address. Example: JohnDoe@email.com
POS_RECON	Optional	Character	1	30		POS reconciliation. POS Reconciliation field to be echoed back in response to POS. Example: RetailPOS1
COUNTER	Required	Numeric	1	10		COUNTER is used for a given MAC label. Each COUNTER should be higher than the last one. This is used to authenticate the POS. Example: 100
MAC	Required	Base64 Encoded Data				Message Authentication Code. This is used to authenticate the POS.
MAC_LABEL	Required	Character	1	50		Associated label that tells the device which MAC_KEY to use to decrypt the value of MAC. This is used to authenticate the POS. Example: REG1

Example

Following is an example of request packet

```

<TRANSACTION>
  <FUNCTION_TYPE>DEVICE</FUNCTION_TYPE>
  <COMMAND>EMAIL</COMMAND>
  <COUNTER>1</COUNTER>
  <MAC> ... </MAC>
  <MAC_LABEL>REG2</MAC_LABEL>
</TRANSACTION>

```

Response Packet

Field	Type	Value	Description
RESPONSE_TEXT	Character		Processor response text. Example: Email Captured
RESULT	Character		This indicates the Result details. Example: OK
RESULT_CODE	Numeric	Expected result code: -1, 59001, 59006, 59040	This indicates the result code. Refer to Result/Error Codes for details.
TERMINATION_STATUS	Character	SUCCESS or FAILURE	This indicates the transaction termination status. This is the overall status of the transaction irrespective of approved or declined. Like, if the output is generated then the status is SUCCESS and if no output is generated then the status will be FAILURE.
POS_RECON	Character	Ex:	POS reconciliation field echoed back if sent in request. Example: RetailPOS1
EMAILDATA	Character		This returns the entered email data. Example: JohnDoe@email.com
COUNTER	Numeric		Echoes counter sent in the request. Example: 100

Transaction Performance Metric

Note

These fields are returned, if SCAPERFMETRIC parameter ([Application Parameters](#)) is enabled.

Field	Type	Value	Description
UI_TIME	Time		This indicates the time duration, for which the device screen is displayed (like error message, prompt screen, remove card screen) till any user action is performed in the command execution flow. This field is not applicable to capture the time for the Processing, Authorizing and transaction status screen. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <UI_TIME>44.028</UI_TIME>

Field	Type	Value	Description
HOST_TIME	Time		This indicates the time taken for the Connection to the host, sending request and receives data from the host. This field also take the cumulative time for multiple requests which may sent to the host during the transaction including two legged transactions, timeout requests, Auto Last Tran requests, DCC, Credit app proxy. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <HOST_TIME>1 . 389</HOST_TIME>
CMD_TIME	Time		This field indicates the total amount of time for a command, which is executed by the application from request received to the response sent. The format of the returned value would be S.sss, where S is seconds (this can be 0 to any positive integer) and sss is milliseconds. In case of any insignificant time or 0.000 value, will not be returned in the response. Example: <CMD_TIME>70 . 765</CMD_TIME>

Example

Following is an example of response packet

```
<RESPONSE>
    <TERMINATION_STATUS>SUCCESS</TERMINATION_STATUS>
    <COUNTER>1</COUNTER>
    <RESULT_CODE>-1</RESULT_CODE>
    <RESULT>OK</RESULT>
    <RESPONSE_TEXT> Email Captured </RESPONSE_TEXT>
    <EMAILDATA> {email address - could be same or different} </
EMAILDATA>
</RESPONSE>
```