



---

[https://verifone.cloud/docs/application-development-kit-version-410/Release\\_Notes\\_ADK\\_4.10.4.6](https://verifone.cloud/docs/application-development-kit-version-410/Release_Notes_ADK_4.10.4.6)

Updated: 23-May-2025

## **Release\_Notes\_ADK\_4.10.4.6**

Release Notes ADK 4.10.4.6

**Released: 2025-05-19**

### **CONFIDENTIAL INFORMATION:**

This document contains confidential information that is the property of Verifone Inc. No part of this document may be copied, distributed, stored in a retrieval system, translated into any human or computer language, or transmitted in any form or by any means, without the prior written consent of Verifone.

### **IMPORTANT NOTICE**

Verifone, the Verifone logo, is a registered trademark of Verifone. Other brand names or trademarks associated with Verifone products and services are trademarks of Verifone, Inc. All other brand names and trademarks appearing in this manual are the property of their respective holders.

### **NO WARRANTY**

No warranty although Verifone has attempted to ensure the accuracy of the contents of this manual. This manual may contain errors or omissions. This manual is supplied "as-is," without warranty of any kind, either expressed or implied, including the implied warranties of merchantability and fitness for a particular purpose.

### **LIMITED LIABILITY**

Limited Liability in no event shall Verifone be liable for any indirect, special, incidental, or consequential damages including damages for loss of business, profits, or the like, even if Verifone or its representatives have been advised of the possibility of such damages.

**Verifone, Inc.**

**817 Broadway, Suite 1100**

**New York, NY 10003 USA**

[www.verifone.com](http://www.verifone.com)

**Copyright © 2025 Verifone, Inc. All rights reserved.**

No part of this publication may be copied, distributed, stored in a retrieval system, translated into any human or computer language, transmitted in any form or by any means without prior written consent of Verifone, Inc.

## Introduction

This document describes the content and changes in the ADK 4.10.4.6 release. It includes details about supported hardware, components used, major changes and bug fixes as well as known issues and updates to procedures.

A summary of planned or implemented incompatible changes, which may require changes to applications, are provided as an annex.

**Please check the installations section, to understand restrictions on downgrading to older ADK versions.**

## Content

This release provides files as follows:

Product Name	Package Name	Component identifies as
ADK Middleware SDK and system load files	adk-full-ext-4.10.4.6-1937.zip	SLP ADK-4.10.4.6
ADK Middleware Documentation	adk-overview-programmers_guide-4.10.4.6-1937.zip	N/A
ADK Middleware Components Release Notes	adk-component-release-notes-4.10.4.6-1937.zip	N/A
ADK System Upgraders	adk-upgrader-4.10.4.6-1937.zip	N/A
ADK V/OS SDK (combined ADK+OS SDK)	adk-sdk-vos-4.10.4.6-1937.zip	N/A
ADK V/OS2 SDK (combined ADK+OS SDK)	adk-sdk-vos2-4.10.4.6-1937.zip	N/A
ADK ANDROID SDK (combined ADK+OS SDK)	adk-sdk-android-4.10.4.6-1937.zip	N/A
ADK VHQ sys config remove package	dl.VHQconfig-remove-prod.tgz	N/A

## Installation

**Important note:** On any Engage device with battery, please calibrate the battery after installing the new version. Go through a complete discharge-charging power cycle at least once.

### Secure Installer note:

- To install user applications for ADK 4.10, you must install a license token before starting the installation process for applications.

- To install user applications for ADK 4.10, you must sign them on the online portal before installing them on the device.
- Please check the appendix "New user signing for V/OS2" below, and the chapter "Guidance for new user signing feature" in the ADK programmers guide.

To update previous releases to ADK 4.10.4.6, please follow the instructions below:

- **Engage:**

- **Please read the section in the programmers guide and in the appendix of this document before use on Engage devices. You may not be able to uninstall user applications otherwise.**
- **Field update**
  - **Field update:** All payment and base devices need be updated to ADK 4.4.5 first when using standard packages.  
By default differential updaters are provided with the release.
- **Deployment**
  - **Prerequisite:** Update device to **ADK 4.4.5** or a newer release.
  - Please use **dl.adk-4.10.4.6-1937-vos2-engage-prod.tgz** to update to this ADK version.
    - Please use the SDI and related packages for other types of devices.
- **Important note: We advise to not cut the power during software updates.**

- **V/OS on Ux:**

- **Important note: Downgrading the SBI boot loader will tamper your device.**
- **For ADK 4.10 there are two types of buildall file for Ux.**
  - **Original buildall (with SBI included) and no\_SBI (new additional buildall). If you use the original buildall file the latest SBI, 3.17.1 will be installed. If you try to downgrade to a build with an older SBI your device will tamper. If you want to keep the old SBI, pre 3.17.1, please use the no\_SBI buildall file.**
  - **The Ux diff update package will not update the SBI file.**
- **Field update**
  - **The following upgraders below are sample updater files for updating UX devices in the field.**
    - **Field update from ADK 4.10:** Update the device to ADK 4.10.4.5 first and then update with **dl.adk-4.10.4.6-1937-vos-ux-diff\_4.10.4.5-1935-prod.tgz**
- **Important note:**
  - **For better behavior of software installs in case of unexpected power failures, we strongly advice to install software in form of compressed tar download files '.tgz' instead of '.tar' files. This note only applies to the top most layer, the download file, no other changes are required.**

- **We advise to not cut the power during software updates.**

## **Solution Package Overview**

ADK 4.10.4.6 provides solution files, which combine the operating system, middleware components and EMV kernel in one single loading image.

**Please review the supported kernel version list and update your desired file accordingly. You must only enable kernel versions, which are certified for your device, country and customer.**

In some cases, due to included user components, solutions might need to be resigned before loading into a unit.

For more details, please check the ADK programmers guide, chapter "ADK Packages and Update Procedure", in particularly "System Installation Download Files".

## **Documentation**

For detailed information on using any of the ADK features, please refer to comprehensive documentation at [adk-overview-programmers\\_guide-4.10.4.6-1937.zip](#).

## **Prerequisites/Requirements**

### **Hardware Requirements**

This ADK release is for use on production hardware terminal units specified in section "Supported Platforms".

### **Software Requirements**

No special software is required for use with this ADK release. This release provides all required software to operate a terminal, except a payment application.

The use of Verifone Development Environment (VDE) is recommended when creating new applications.

## **Release Overview**

ADK-4.10.4.6 is a hot fix on top of ADK 4.10.4.5

The release fixes a backlight issue on E280 devices and is in full parity with ADK 4.10.4.5.

Branch maintenance policy: Please consider moving to ADK 5.0 to pick up latest features and support for the newest Verifone models when updating customer solutions.

### **Supported Platforms**

**MX and VX VOS devices and all Verix eVo devices are only supported on ADK 4.4, not supported on ADK 4.6, 4.7, 4.8 & 4.10.**

## **Carbon 8 and Carbon 10 devices are only supported on ADK 4.6.**

### **This ADK release targets the following Verifone products:**

- Engage: P200, P200 Plus, P400, P400 Plus, V200, M400, V400c, V400c Plus, P400 Dual MSR
- Engage Portable: V200t, V205c, V210, V240m, V240m Camera, V400m, E280 Speaker, E285, E235
- Engage: CM5, M440, M424
- Trident: UX300, UX301, UX410 and Ux115 (for application development only!)

Important note: Use CM5, M440 and M424 only in combination with an approved Android OS version. The same requirement applies to Carbon 8 and Carbon 10 using ADK 4.6.

## **Component Versions**

This ADK Release provides following component versions:

- Abstraction
  - Crypto Abstraction 1.4.2
  - Reader Abstraction 1.7.6
  - Reader Synchronous Cards 1.0.6
- ADK Fonts 1.6.1
- Agent - System remote management (e.g. VHQ):
  - AGT 5.1.5.2 - System Remote Agent
  - AGT-SUBDEV 4.3.40.2 - System Remote Agent for Android Subdevices (e.g. CM5, M424 and M440)
- AST 1.9.2 - Anti Skimming Tool
- Base Updater 1.0.2 - Updating base software
- CCP 1.80.0 - Communication Control Panel
- COM 2.143.0 - Communication service
- CPL 2.8.3 - Commerce Platform Library
- EMV CT, CTLS and MSR Card Services
  - CRD 5.2.131 - EMV service
  - CRD-SYNC 1.3.0 CRD-SYNC service
  - MSR 2.10.3 - MSR service
  - TEC 2.9.6 - Technology selection service
- CTLS L1 Library 1.2.50
- EVT 2.6.18 - Event service
- FPS 1.3.3 - Fingerprint Sensor Library
- GDA 1.0.5 - Global Diagnostic Application
- GUIPRT 2.58.2 - Graphical User Interface service
- INF 1.16.13 - Information Database service
  - SQLITE 1.3.6
  - EXPAT 1.1.9
- IPC 1.31.0 - Inter Process Communication
  - IPC-CFG 1.0.17
- ISO8583 1.6.1 - ISO8583 protocol Communication
- LOG 2.21.0 - Logging service
- NAV 1.1.0 - Navigator Gateway
- NAVLib 1.6.11 - Navigator Library

- NFC 1.19.0
  - NFC VAS 1.11.2
  - NFC Applepay 1.13.4
  - NFC VWI 1.14.3
- REGEX 8.41.3
- PACKMAN 1.7.0 - Tool for managing archives
- PERSO 1.3.0 - Ux Personalization
- PP1000 1.3.0.3 - Pinpad communication library
- PRX 3.8.0 - Cloud proxy
- SBI 3.17.1 - Secure Boot Image
- Secure Data Interface - SDI:
  - SDI 4.30.2-243-P2PE-1.6.28 - Secure Data Interface
  - SDI-API 1.18.0 - High level C++ client library
  - SDI-CLIENT 1.32.0 - Compatibilty layer
- SEC 2.5.3 - Security service
- SKIMMERDETECT 1.0.3 - Anti Skimming Tool Library
- SLP ADK-4.10.4.6 - Solution package version
- SOUND 1.2.8 - Sound library
- SYSTEM SERVICES components
  - SYSINFO 3.106.2 - System Services
  - SYSMAC 3.85.4 - Multi application controller
  - SYSPM 1.44.31 - ADK Power management
- VCL 12.7.6 - VeriShield Crypto Library
- VOS-MSR 1.3.5 - MSR Decoder Library
- VRK-Agent 1.0.5 - Key Injection Service

V/OS:

- OS and SDK 32410800

V/OS2:

- OS and SDK 32410800-A500

CTLS:

- **V/OS**
  - VOS\_CTLS-4-01.30.03
    - Subversion A4/A5/A6: With Visa MSD and Interac (suitable for the Americas and Europe)
    - With ExpressPay 3.0 / 3.1 and PayPass 3.0.2 / MCL 3.1.1 - Combinations according to release notes
  - VOS\_CTLS-4.01.16.13
    - Subversion A4: With Visa MSD and Interac (suitable for the Americas and Europe) - With ExpressPay 3.0 and PayPass 3.0.2
    - Subversion B4: With Visa AP and ePAL (suitable for Asia-Pacific) - With ExpressPay 3.0 and PayPass 3.0.2
- **V/OS2 - CTLS L1**
  - ctls-11-full-1.2.50 CTLS level 1 library for Engage

Tools:

- Windows USB driver (for Trident, Engage) 5.0.5.2 Build 8
- Windows USB driver (for PP, Qx, Nurit) 1.0.0.21 Build 2

## Dependencies

- ADKTMS 5.1.5.2 or higher is compatible with the VHQ Server 3.27.01.19

VHQ XSD version 04.01.0009 is used in this Agent

## Important Notes

- **From ADK 4.10.0 and ADK 4.8.24 onwards if you downgrade to any older ADK 4.8, 4.7 or 4.6 version you will lose any keys on your device.**

## New Features

New features in ADK 4.10.4.6:

- No new features

New features in ADK 4.10.4.5:

- No new features

New features in ADK 4.10.4.4:

- No new features

New features in ADK 4.10.4.3:

- No new features

New features in ADK 4.10.4.2:

- No new features

New features in ADK 4.10.4.1:

- No new features

New features in ADK 4.10.4:

- **Android SDK:** All components provided in the Android SDK are now built against NDK version 26.2.11394342

- Wifi: Enabled more channels for various countries for mainly the 5 GHz band. It is recommended to update to this ADK 4.10 version, when experiencing issues with supported Wifi bands

#### New features in ADK 4.10.3:

- SEC: Hardened the implementation of file access and use of compression libraries when used by system services; removed telnet library from the default solution
- MST: Added support for MST pay to more Engage devices
- Contact EMV: You can now configure the version of the EMV contact L1 driver, in case your device supports multiple versions. Please check the EMV documentation for details and make sure, that the version matches to what you have referenced in other certifications.
- COM: VOS2 orange accessory dongle support has been extended to cover additional use cases. Please check the COM section of the ADK Programmers guide for details
- Battery logs: Reduced unneeded log printing  
Sysmode: Added diagnostic menu for battery  
Battery: Improved battery charging management (charging level display)

#### New features in ADK 4.10.2:

- COM: added support for MFI to e235
- Secure Installer: VOS2 now allows targeting for lists of serial numbers
- Battery related changes:
  - e235 battery charging maximum temperature updated to reflect value in updated battery cell data sheet.
  - Force reset of reported battery % to fuel gauge device value if repeated short resume periods do not allow S/W derivation for 20 minutes.
  - Fault battery status logged in tamper log to help with fault diagnosis.
  - Improved charging management on depleted battery.

#### New features in ADK 4.10.1:

- SDI: the number of digits after the decimal point is now currency specific and supports 3 digits

- The Device Software Licensing and Protection (SLP) status is now displayed on the VOS1 boot splash screen and in the Sysmode. Please find a more detailed description in the ADK Programmer's Guide/System Diagnosis and Troubleshooting/Device Software Licensing and Protection status guide

## Fixed Issues

### Fixed Issues in ADK 4.10.4.6:

- Portable and Mobile
  - Power mgmt: Added a power mode in VOS2, which doesn't turn on the backlight to allow running background tasks. Please check the programmers guide for more details.

### Fixed Issues in ADK 4.10.4.5:

- All Engage
  - Bluetooth: Fixed several issues:
    - Disabled implicit pairing feature in lower Bluetooth stack as it is not supported by Engage.
    - Fixed various connection/disconnection bugs when using Bluetooth Apple iAP2 or Android PMRMUX2 protocols.
    - Bluetooth: To prevent implicit pairing, the retry mechanism for missing keys is now disabled.
- Portable and Mobile
  - Battery: Fix to battery % being briefly incorrectly reported as 0% after a suspend period longer than 20 minutes.
  - Bluetooth: Improved robustness of Bluetooth HW driver connection for e235.

### Fixed Issues in ADK 4.10.4.4:

- All Engage
  - NFC: Update Applepay and VWI kernels for compatibility with modified function call names in OpenSSL3.
- Portable and Mobile
  - COM-WIFI: Added "WPA-EAP-SHA256" key management mode in order to operate on an AP with WPA2/3" Mixed Mode.
- PinPad
  - P400 Plus touchscreen: Improved detection and recalibration of large objects on screen.

- COM-WiFi: Implementation: After terminal's reboot country domain is set automatically to world regulatory domain 00, which is used to select a behavior (1) or (2).
    - (1) Country Code isn't changed/specified by user. World regulatory domain is configured.
    - Behavior: Country Code can be set automatically during scan procedure or upon a connection to wireless Access Point, if AP is transmitting Country Code information element in Beacon/Probe Response/etc. frames.
    - (2) Country Code is changed/specified by user via ADK-COM API. Then svc-net automatically sets this Country Code upon power on of WLAN module.
    - Behavior: WLAN stack is ignoring Country Code, which is transmitted by wireless AP.
  - COM-WIFI: Fixed an issue, where the previous addition of new "WPA-EAP-SHA256" key management mode caused issues on some devices that do not support this key option.
- Desktop
    - COM-WIFI: Fixed an issue, where the previous addition of new "WPA-EAP-SHA256" key management mode caused issues on some devices that do not support this key option.

#### Fixed Issues in ADK 4.10.4.3:

- Portable and Mobile
  - BT: Several optimizations were implemented for reconnection time reduction: reworked event Thread, reduced sleep intervals, removed unnecessary scans and also optimized XML parsing.
  - BAT: Fixed issue with battery not reporting correct percentage on e235

#### Fixed Issues in ADK 4.10.4.2:

- Portable and Mobile
  - VHQ: Fixed an issue which prevented installation of JSONKeyBlobs provided by the VHQ server.

#### Fixed Issues in ADK 4.10.4.1:

- All Engage
  - CCP: Corrected an issue, where a wrong label is shown in com control panel during start of the interface
- Portable and Mobile
  - COM/CCP: Improved the behavior of configuration DB updates for CCP and COM. Please check the chapter Example 7: WiFi configuration for roaming in the ADK programmers guide, in component ADK-CCP for details.

- BAT: Descriptive battery levels (low, critical etc.) now correctly aligned with numerical % ranges. Also capacity reporting improved for short resume periods during repeated suspend-resume cycles.
- VOS-BT: Fixed a sporadic issue, where the device had to be restarted after a BSA server disconnect.
- BAT: Descriptive battery levels (low, critical etc.) now correctly aligned with numerical % ranges. Also capacity reporting improved for short resume periods during repeated suspend-resume cycles.
- COM: The CCP database update mechanism was enhanced by adding a new parameter to control the WiFi roaming. Previously, if new WiFi configurations were added through this mechanism, the roaming capability had to be activated manually using the CCP UI.

#### Fixed Issues in ADK 4.10.4:

- All Engage

- VCL: The AES DUKPT group "usr0"/"usr1" keys in VCL has been updated
  1. "usr1(128/256 byte length)" keys can be downloaded. If both "usr0" and "usr1" keys are present, "usr1" key will always take priority
  2. Keys for "usr0" and "usr1" must have different IKID (initial key id) to co-exist. If the same IKID is used, "Failed TR-34 JSON install" message will be displayed on terminal
- Wifi: Updated the wireless regdb regulatory database to the version of 2024, January 23rd  
Wifi: Engage devices, except devices based on CYW43340, now support Wifi Fast Transition (FT), if 802.11r and 802.11k is enabled on the router. Please check the documentation of your access point for details, no configuration on the device is required.
- COM: Fixed an issue in BT where iPhones can't successfully paired and unpaired when disconnected while pairing

- Portable and Mobile

- PM: Added a display configuration "backlight\_control" to control, if ADK-PM should manage the display brightness.
- Radio: Issue with SIM from carrier Orange fixed for mobile devices. Power-up sequence adapted as per Quectel radio module specification.
- COM: Issue with serial Bluetooth connection to POS fixed.

- COM: Existing configurations in the com database for IP, DNS or network masks for a static IP set-up are now shown in the control panel after turning off DHCP.
- VOS-RADIO: Modifications have been made in the case of LTE Attach #11, #12, #13, #14, #15, #22, #35, #42 to ensure compliance with the 3GPP standards.
- Unattended
  - SYS: MX downloader is now able to sync date/time of UX300/301 with a PC again. A new MX downloader version is not required

#### Fixed Issues in ADK 4.10.3:

- All platforms
  - Fixed an issue that activation of Mifare Ultralight and Classic failed on All platform
  - Fixed an issue when VAS is enabled, terminal is unable to perform Contact and MSR transactions
- All Engage
  - COM: Events generated by the PPP\_USBD interface now report correctly as PPP\_SERIAL, and no longer report as LAN events
  - Documentation: The missing content in the ADK COM part of the ADK programmers guide is now added again
- All VOS3 and Android 10
  - Signature capture: GUI now allows setting the DPI value for TIFF signatures
- Portable and Mobile
  - NFC: Fixed an issue with MiFare support on e280
  - VHQ: Older payloads now get rejected if, a usr1 package with a newer DID is already installed
  - Cellular radio: Fixed a sporadic issue for some radio modules of V400m, where the device is unable to reconnect to a network, when it enters coverage again
  - Mifare: Fixed a card reading issue for some cards in Mifare encryption state
  - WiFi: Wireless regulatory DB has been updated to the latest release - 2024-01-23

- COM: The ELS31-J radio module for V400m is now supported
- Low power modes: Fixed a sporadic hang condition when trying to update the status bar after waking up from deep sleep mode
- EHS6 cellular radio: Run SIM status check again in SIM switch in case a SIM BUSY status is returned, to ensure the SIM status is shown correctly
- NFC: Added FeliCa-LiteS support
- CRT reset: Fixed a error -213 issue when executing Cert resets through VHQ
- Wifi: Implemented standards of WLAN Fast Roaming (IEEE 802.11r/k)
- PinPad
  - CTLS: Google SmartTap: Added Generic ('gr') and Generic Private ('gp') pass support for Google Wallet cards in NFC lib
  - NFC: Added FeliCa-LiteS support
  - COM: Fixed an issue where web-sockets cannot be connected, if the set-up of a socket is cancelled, while the connection is being established
- Desktop
  - NFC: Added FeliCa-LiteS support
  - Port redirection tool: Fixed an issue with the port redirection tool, which prevents it from running on V205c
- Unattended
  - VHQ: Fixed an intermittent VHQ agent issue, where heartbeats were skipped for several minutes.
- Multi-lane
  - USB: Improved mechanism for USB cable connect/disconnect detection for devices connected to the Engage side for mixed Android and Engage devices

Fixed Issues in ADK 4.10.2:

- All platforms

- SDI: Support EMV Contact Read Card Data Transactions with Online PIN
- Portable and Mobile
  - Radio: Improved processing of CPIN messages
  - VOS-BT: Fix scenario where SVC-NET could crash after BSA server is killed
  - COM: Basic GSM info like IMEI and Module type now can be retrieved without SIM being present in device.
  - GPRS connection failures (radio: PDP context 1 is not updated in some cases)
- Multi-lane
  - GUI: Added second timeout for remote rendering service (ARRS) for M440

#### Fixed Issues in ADK 4.10.1:

- All Engage
  - PIN pad: Fixed an issue with pairing of pin pads with SDI
- All Trinity
  - SDI: harmonization of error codes between SDI Server running in headless or standard mode so both return 0x6405 in case of Card Removal at PIN Entry
- Portable and Mobile
  - Sysmode: Version display for e235 devices now shows the serial number properly
  - Radio: fix crash issue with the IMEI reading mechanism on devices with a Telit radio module.
  - Display: The touch configuration for V240m with display adc\_val 1235 has been changed to eliminate "ghost touches"
  - Android SDK: Fixed an issue, where wrong IPC binaries could be picked up during the build accidentally
- PinPad
  - COM: Previously CCP synchronizes database updates with libcom only for eth0, wlan0 and gprs0 interfaces. Updated to include IP over USB.

- SDI: harmonization of error codes between SDI Server running in headless or standard mode so both return 0x6405 in case of Card Removal at PIN Entry
- Desktop
  - Radio: fix crash issue with the IMEI reading mechanism on devices with a Telit radio module.
- Multi-lane
  - NFC: Unsupported cards were not handled correctly, polling results analysis has been improved. "Card Not found" case has been reimplemented

## Known Issues, Limitations and Restrictions

### Known Issues:

- No known issues

### Restrictions:

- **Hardware support:** Please check the official PCI web page for support of any given hardware. This is a new release line and certifications may still be in progress.
- **From ADK 4.10.0 and 4.8.24 onwards, if you downgrade to any older ADK 4.8, 4.7 or 4.6 version you will lose any keys on your device.**
- **VHQ Agent 2.17.x or above should be used with VHQ server 3.11.27.x or higher.**
- **VHQ Agent 3.2.5 or above should be used with VHQ server 3.12.02.06 or higher.**
- **VHQ Agent 3.2.16 or above should be used with VHQ server 3.14.02.16 or higher.**
- **VHQ Agent 3.4.1 or above should be used with VHQ server 3.19.01.18 or higher.**
- **VHQ Agent 3.4.2 or above should be used with VHQ server 3.21.0.14 or higher.**
- **VHQ Agent 5.1.3.x or above should be used with VHQ server 3.24.01.19 or higher.**
- **VHQ Agent 5.1.4.x or above should be used with VHQ server 3.26.01.17 or higher.**
- **VHQ Agent 5.1.5.x or above should be used with VHQ server 3.27.01.19 or higher. Please**
  - Check server version before recommending device software updates (especially on-premise clients).
  - Check version of Agent that will be included in any device software update.
  - Check version of software embedded on any devices before distributing to clients.
- **V200t: You must use the latest PVT-3 battery. Low power modes cannot be used on V200t. The unit may hang sporadically and needs to be rebooted.**
- **Reboot when updating applications:** When updating user package, the device will now always reboot. The only exception from this behavior are user data files.
- "When upgrading to ADK-4.4.17/ADK-4.6.4/ADK-4.7.x/later versions from older versions, it is recommended to go through a complete discharge-charge power cycle atleast once after the SW update. For later updates, example moving from ADK-4.6.12 to ADK-4.7.6 this step is not required. If battery is removed and re-inserted, it is recommended to go through a complete discharge-charge power cycle atleast once.

- The presence of countries with WLAN channels supporting in the list does not indicate that the product is fully approved for use or sales in all listed countries.

**Please follow the update procedure above strictly. There are several limitations in older releases regarding the update of units:**

- For releases earlier than ADK 4.4.0 and ADK Portable, do not use combined Engage download packages. Device specific download packages must be used for ADK 4.3.x, ADK for Carbon and ADK for M400 and older releases.
- **Engage automated update:** In some cases, the unit may not automatically restart after an install. Please reboot the unit manually in that case.

## Appendix:

### General notes:

- **For all Base devices:**
  - Devices without user signed VHQ Config - in the field:
    - will receive a sys6 signed VHQ config with current ADK release. This config will set the operating mode to "Direct". Once user decided to install a user signed VHQ Config, a package "dl.VHQconfig-remove-prod.tgz" needs to be installed first. Please contact Verifone service team for assistance.
  - Devices without user signed VHQ Config - out of the box scenario:
    - While installing user signed VHQconfig pointing to customer server, please do not use "ADK operating mode", but "Direct mode" instead.
  - Devices with user signed VHQ Config package:
    - Must ensure that **VHQ config is set to use Direct mode** before installing this version of ADK.
    - During installation of this ADK will see an error message where sys6 signed VHQ config will fail to overwrite existing user signed VHQ config. Please ignore error message.
- **VOS2:**
  - Radio auto-start must be used if the radio needs to be turned off for any reason. Auto-start is the default and it should be retained in this release.

### SW Update Capabilities

- **Buildall**
  1. Surgical removal - removed OS+sys apps - but not usr apps or keys or OS config; however, network settings will be reverted to default (package "cdgnetcfg").
  2. Loaded via USB or as a package i.e. downloadable file via VHQ, netloader, etc...
  3. Used at deployment center to change factory VOS into that required by customer.

4. VHQ:
  1. In the past, VHQ device-specific session key was deleted, but fixed in Agent R6 and later.
  2. Currently
    1. Using the normal build all will erase all settings for VHQ.
    2. However, we can technically generate a “upgrader”, (see below) which only erases downgraded components. This should be reviewed in advance for any security breaches (usually there is none), and then be used in VHQ.
    3. However, this is a one off process, i.e. a usual updater request.
5. In most cases, can downgrade, i.e. change to earlier VOS release. Note on MX9, downgrading from release-3014 to something earlier requires special magic, contact i\_mx\_T3SW for details.
6. This does NOT wipe Warranted Keys / VRK key.
7. VCL:
  1. in the past, VCL Keys, Configuration Data, and the BIN Table file was deleted with a build-all.
  2. Starting with VCL 9.1.001S (in OS release-31040101) VCL now stores the VCL Keys, Configuration Data, and the Bin Table file into a new folder location so the build-all will not delete these files.

- **Removeall**

1. Remove file in a bundle - list off what you want to remove. Can remove everything that was loaded via a bundle (anything part of manifest) i.e. not anything that apps created.
2. Secure Installer API - remove bundle names, users (same limitations as remove file via bundle).
3. Never do a removeall on its own of OS (without OS as part of buildall) because then you'd have no OS.

- **Crtreset**

1. Tool that uses customer signer card to be able to remove customer app sponsor. Required when device is no longer being used by customer.
2. (info) this is used by customers for their devices (works with customer specific app sponsor only).
3. Passwords are set to pre-expired such that user is forced to enter new passwords.

- **Upgraders**

1. Use a script to determine if upgrade applicable, based on current software installed, e.g. VOS release/build string.
2. "Upgrades", so changes nothing if already on final VOS build, or applied accidentally to a later VOS release/build, i.e. "upgrade to release-30250600" downloaded when release-30410400 running on device.
3. Script can remove specific files or packages if no longer relevant. E.g. MX9 VOS ADK 2 and ADK 3, FLTK and Nano-X were optional packages in their own bundle. For release-3041 it was moved into the core.

4. During upgrade, a package can be replaced with more-recent version, or altered using **bsdifff** (does binary patching of package). However, **bsdifff** requires a specific package version to start with.
5. Overhead is (at least) one extra reboot that a build-all does not need. This is when the upgrader script runs to decide what to do.
6. MX9 Upgraders must not change VCL, VHQ and its certificates, CTLS, and not touch vos-syslog-flash package.

- **Tamper / VCL Key**

Note about VCL keys specifically and key versus config in bold below

**In AES DUKPT mode the keys are now handled and stored by the OS so the keys shouldn't be lost during a buildall. But the other VCL configuration settings would be lost temporarily disabling encryption until another VCL config package is installed on the device.**

As documented above in the VCL section, configuration data and the keys used in DDK mode have been moved to a new location under VOSCOR-21681 which will be integrated into the OS after QA completes testing. The new location will persist keys and data after a build-all.

- **Permanent Tamper**

- AKA: TANC (tampered and not cleared) is a tamper that is still physically active e.g. a normally closed tamper switch is open, or a security mesh is broken.  
The source of the tamper must first be fixed in hardware before the terminal can be detampered.

- **Transient Tamper**

- AKA: TAC (tampered and cleared) is a tamper that was physically active e.g. a normally closed tamper switch opened and then closed, or a security mesh was temporarily open but is now closed.  
By definition, for a transient tamper the source of the tamper has first been fixed in hardware, so the terminal can be detampered.

- **Tamper Handling**

- Tamper detection and response are done entirely by the hardware, when a tamper event occurs the vault code that deals with the tamper events manages the tampering logs messages and deliver these log messages to the public world.

A tamper will always reboot the terminal. All secret or private keys, or the key that is encrypting them, are deleted.

On every boot up, the software determines the tamper status.

There are two ways the terminal

software can respond if the terminal is tampered:

- Not run any third party applications.
- Run third party applications but disable all payment interfaces such that payment (or processing of cards MSR, Contact, Contactless, or card data) is not possible.

A terminal may support either one or both of these methods. The configuration of which methods are supported is done at manufacture time by setting a signed Secure Installer variable.

- ○ **Detamper device**

There are two methods to detamper a device, it may support either one or both of these methods.

- Detamper with passwords / direct key load operation.
- Detamper with SST (Secure Service Tool TRSM) / Keyloading via KLD.

The configuration of which methods are supported is done at manufacture time in a MIB (Message Information Block) file. This configuration cannot be changed once set.

## Tables:

- **Key Wiping Scenarios**

### Symbol

### Meaning

- ? The keys will not be affected in this scenario
- ? The keys will either be deleted or rendered unreadable and unusable
- ?? The keys will be replaced with new versions

Key/SW vs Scenario	War- ranty Keys	Cus- tomer Key IPP	Cus- tomer Key ADE 3*	Cus- tomer Key VSP	Cus- tomer Key AES DUKPT	VSS Script Key	Apple/ Google Wallet Key 2*	App	ADK (USR)	ADK (SYS)	OS config	OS	VSS Scripts	Pass- words
Buildall	?	?	?	? 1*	?	?	?	?	?	?	?	?	?	?
Buildall + Remove all User	?	?	?	? 1*	?	?	?	?	?	?	?	?	?	?
Remove all	?	?	?	?	?	?	?	?	?	?	?	?	?	?
Remove all users	?	?	?	? 1*	?	?	?	?	?	?	?	??	?	?
CrtReset	?	?	?	?	?	?	?	?	?	?	?	?	?	?
O/S Upgrade	?	?	?	?	?	?	?	?	?	?	?	??	?	?
ADK Upgrade	?	?	?	?	?	?	?	?	??	??	?	?	?	?

Application Upgrade	?	?	?	?	?	?	?	??	?	?	?	?	?	?
Tamper Event	?	?	?	?	?	?	?	? 4*	?	?	?	?	? 4*	?
CP Dev	Replaced with test keys	?	?	?	?	?	?	?					Replaced with test keys	?

**Notes:**

1. In the past VHQ device-specific session key was deleted, but fixed in Agent R6 and later.
2. This is a app key transported via VSS key.
3. Note that ADE requires a FeatureEnablement license token to enable it (in addition to an ADE key).
4. For Brazil ABECS it is a requirement to delete the applications on tamper.
5. Diagnostic counters are always maintained as long as coincell is good (they are in Battery Backed sram).

**ADK re-packaging**

**Status of change**

Type of change      Repackaging of full-ext zip archive

New behavior available      ADK 5.0

Planned Deprecation version      ADK 5.1

ADK components      ADK integration and packaging

Changes      The ADK-full-ext zip archive is replaced by SDK archives, a doc archive and platform specific load archives.

Impacts      As a solution provider you may need to update build scripts to use the new zip archives instead of the full-ext zip archive.

Transition: The original full-ext zip archive is still available and can be used to simplify the transition.

Reasons for change      With the introduction of VOS3, the size of the ext-full bundle becomes unmanageable large. As some parts are already provided separately, the remaining files will be split, too.

References      Packaging documentation in the programmers guide.

## PCI version check

### Status of change

Type of change Add ability verify consistency of PCI versions from sysmode and via API

New behavior available ADK 4.10 / ADK 4.9

Planned Deprecation version N/A

ADK components Installer and sysmode for VOS1 and VOS2

Changes A new API was added to verify, if the combination of installed components match the expected and certified combination and reported a "tainted" status, if they do not match. The same check is added to sysmode and the PCI version splash screen shown during start up. In addition a NAG screen is implemented on devices with color screens, which will be shown during regular operation, indicating a tainted state.

Terminal users should check for tainted status of terminals in the field in a similar way as checking PCI versions.

Impacts Solution providers must use a full ADK stack to not risk a tainted device or loss of functionality.

Application developers can check the status and report to servers or show the status on application status screens. This is particularly important for headless devices like UX300, UX301 or UX410, if operated without UX100.

Reasons for change Security: Although installations are password protected and should prevent installation of unwanted combinations, the tainted state mechanism was added to counter the increasing complexity of the system and simplify verification of certified version combination.

References Secure installer interface documentation

**secRSAPrivate() / SDI Remote Key Service - will no longer accept RSA keys with key usage 'K3' "Asymmetric Key Pair for Key Wrapping/Key Agreement".**

**Status of change**

Type of change Added restriction on key usage.

New behavior available K81 FW: SPFW\_01.05.xx.xx (release line: 1.4.x)

Planned Deprecation version K81 FW: SPFW\_01.05.xx.xx (release line: 1.4.x)

ADK components VOS3 / VAOS10

Changes secRSAPrivate() / SDI Remote Key Service will no longer work with RSA keys with key usage 'K3'.

Impacts No impact is expected as the ADK provides signing and data decryption functions, but not key wrapping / agreement. Key usages 'D1', 'S0', and 'S2' will continue to be supported. Besides, VRK key profiles reports confirm that no keys with key usage 'K3' were created for that purpose.

Security:

Reasons for change Turkey Custom RKL to be implemented in the planned deprecated version, requires loading an RSA key with key usage 'K3' for decrypting the payloads. This RSA key is accessible to apps that can potentially use it with secRSAPrivate() / SDI Remote Key Service to decrypt payloads on the non-secure side.

References

## **Packages trying to install files to /mnt/flash via their /home subdirectories would fail to install**

### **Status of change**

Type of change Restrictions enforced on installation packages to make those comply with the Secure Installer specification from the ADK programmer's guide.

New behavior available All major ADK branches.

Planned Deprecation version

ADK components VOS/VOS2

During installation, Secure Installer prevents installation of files outside the directory tree of a package, even when using symlinks and enforces the behavior described in the installer documentation.

- Changes
- This applies specifically to user home directories like /home/usr1 and affects files in /mnt/flash, even if they are accessible via a symlink from the user home directory.
  - Secure installer allows the use of symlinks even during installation, as long as all files for usr1 will be extracted to - and only to - the /home/usr1/ subtree.
  - To install files to /mnt/flash, a dedicated SI installation package with "userflash" type must be used. This means, that the usage of the "flash" directory is not allowed in regular user packages.
  - Please consult the secure installer documentation for more details

Packages not complying with this rule fail to install.

Impacts Customers using packages that contradict Secure installer specification.

Reasons for change Reduce the attack surface.

References dl files can be verified with packman, starting version 1.4 with the validate command "packman.py validate -t vos2 -rd dl.file.tgz"

## Remove "Unsigned packages" from VOS/VOS2

### Status of change

Type of change Remove support for installing "Unsigned packages"

New behavior available ADK 4.10

Planned Deprecation version N/A

ADK components VOS/VOS2

Remove support for installing "Unsigned packages"

Changes

- Installation packages that do not require signature, used for installing media files to device, will no longer be supported.

Impacts Customers using "Unsigned packages" will require to use alternative methods for downloading media files to their application.

Reasons for change      Reduce the attack surface.

References

## **Old internal CWK APIs marked as deprecated for the compiler**

### **Status of change**

Type of change              Old internal CWK APIs marked as deprecated for the compiler

New behavior available      ADK 4.10

Planned Deprecation version ADK 4.7

ADK components              VOS/VOS2

Following VOS/VOS2 internal APIs marked as deprecated for the compiler

Changes                      

- cryptoRead
- cryptoWrite
- cryptoReadWrite

Users compiling their applications against old CWK APIs.

This should not be done, starting with ADK 4.7.

Impacts                      ADK-SEC public APIs must be used instead:

- secEncryptData
- secDecryptData

Reasons for change              Gradual deprecation of replaced internal OS CWK APIs.

References

## **Remove 'voltagesecurity' library from VOS1 build**

### **Status of change**

ADK components              VOS1

Type of change              Remove 'voltagesecurity' library from VOS1 build

Changes                      Remove 'voltagesecurity' library from VOS1 build

Impacts                      No one.

Reasons for change                      During upgrade to openssl3 dependencies in 'voltagesecurity' library on VOS1 were identified.

No users for the library were identified.

New behavior available                  ADK 4.10

Planned Deprecation  
version

References

## **VOS2 VRK "key name" length limited to 32 chars**

### **Status of change**

Type of change                              VOS2 VRKv1/VRKv2 "key name" length limited to 32 chars

New behavior available                  ADK 4.9

Planned Deprecation  
version    ADK 4.9

ADK components                              VOS2

Changes    User will be able to load only VRKv1/VRKv2 payloads with "key name" field length < 32 chars.

Impacts    VRKv1/VRKv2 payloads.

Reasons for change                              Internal legacy OS structures do not allow handling longer key names.

This solution resolves bugs related to handling of longer key names.

References

## **MSR Service removed**

### **Status of change**

Type of change                              MSR Service removed

New behavior available                  ADK 4.9

Planned Deprecation version ADK 4.9

ADK components                              VOS1, VOS2

Changes	MSR is now a middleware component. Using "libvfimsr" is now deprecated, the "libvfimsrwrap" should be used instead.
Impacts	Applications that use msr_svc calls have to substitute these with the new library. You must use the ADK package to load the SW or lose some of the functionality.
Reasons for change	MSR driver and decoder enhancements
References	

## Sysmode file browser removed

### Status of change

Type of change	Sysmode file browser removed
New behavior available	ADK 4.9, 4.8, 4.7
Planned Deprecation version	
ADK components	VOS2
Changes	Sysmode file browser exposed files to user that can be used in the vulnerability exploit. Sysmode file browser removed.
Impacts	Sysmode file browser
Reasons for change	Device security
References	

## Deprecate ADK-EVENT APIs

### Status of change

Type of change	Deprecate ADK-EVENT API on ADK 4.9
----------------	------------------------------------

New behavior available

Planned Deprecation version ADK 5.1

ADK components ADK-EVENT

Changes ADK-EVENT component functionality is covered by ADK-IPC API. See the ADK-IPC Programmer's Guide for detailed information.

Impacts Access to ADK-EVENT API

Reasons for change Obsolete functionality

References

## Access to the sysmode-www for Bases removed

### Status of change

Type of change sysmode-www removal,  
new menus on the handset's sysmode to configure a connected base

New behavior available ADK 4.8.14, ADK 4.9

Planned Deprecation version

ADK components VOS2

Changes

- access to the sysmode-www removed from bases
- new menus on the handset's sysmode added (only Engage handset's):
  - new menu "Base Config" under the "Administration" if the handset is docked and paired with a base
    - sub-menu "Date/Time" to configure the date and time on the base
    - sub-menu "Static IP" to configure the static IP on the base
    - sub-menu "Unpair all handsets" to unpair all handsets that are connected to the base that is connected to the current handset

Impacts sysmode-www removed from V400m base, V240m base, V210 base, CM5 base, T650p base  
new menus on Engage handsets only.

Reasons for change Vulnerabilities on the sysmode-www

References

## OpenSSL upgraded from 1.0.2 to 3.0

### Status of change

Type of change	OpenSSL upgrade
New behavior available	ADK 4.10
Planned Deprecation version	ADK 4.10 Attention: This change will <b>not</b> be back ported to existing branches
ADK components	VOS1 & VOS2
Changes	OpenSSL version on the device will be upgraded to 3.0
Impacts	All Engage and Ux users
Reasons for change	<ul style="list-style-type: none"><li>• OpenSSL 1.0.2 reached end of life.</li><li>• OpenSSL 3.0 adds TLS 1.3 support</li></ul>

References

## The minimal sysmode password length now is 7 digits on all Engage and Ux

### Status of change

Type of change	Sysmode password length validation
New behavior available	ADK 4.9

## Planned

Deprecation version Attention: This change will be not backported to existing branches

ADK components VOS1 & VOS2

Changes If the current sysmode password value on a device is less than 7 digits long, then, during the next login the user will be prompted to enter a new password value that is at least 7 digits long.

This change affects only users who change the password by password update/reset packages and set the new password that is less than 7 digits.

Impacts All Engage and Ux users

Reasons for change PCI and security requirements

References

## Drop networkapps service

### Status of change

Type of change Remove library from default integration

New behavior available ADK 4.8

Planned Deprecation version Attention: This change will be backported to existing branches

ADK components ADK SYS on VOS1 & VOS2

Changes Remove library integration of "libsvc\_networkapps.so"

This library was delivered as part of "vfiservices" package in "svcmgrstk" bundle

Impacts No impact, as not used

Reasons for change reduce RAM usage, download size and maintenance

References

## Remove extra packages from V/OS1 integration

## Status of change

Type of change	Remove packages from default integration:
New behavior available	ADK 4.8
Planned Deprecation version	
ADK components	VOS1 ADK integration
Changes	<p>Remove packages from default Ux integration:</p> <ul style="list-style-type: none"><li>• skimmerdetect - there is no AST support for Ux units (Mx units are not supported in branches higher than ADK 4.4)</li><li>• libcpr- commerce platform is disable by default on V/OS1 units</li><li>• libfps - no finger print scanner on V/OS1 units</li><li>• libcpapp - commerce platform is disable by default on V/OS1 units</li></ul> <p>The packages libcpr and libcpapp can be loaded with an application, if required</p>
Impacts	Installations on ADK 4.8.x
Reasons for change	reduce RAM usage on UX units
References	

## Drop bzip2 compression support for dlfiles/bundles/packages

### Status of change

Type of change	Remove of packaging format Bzip2 compressed (extensions: tar.bz, tbz, tbz2) Use Gzip instead (extensions: tar.gz, tgz)
New behavior available	ADK 4.4 and previous releases support tgz and tar
Planned Deprecation version	Attention: This change will be backported to existing branches

ADK components	VOS-SI
	Secure Installer on VOS2 will not support the Bzip2 decompression (extensions: tar.bz, tbz, tbz2) methodology in future for:
Changes	<ul style="list-style-type: none"> <li>• dlfile</li> <li>• bundles</li> <li>• packages</li> </ul> <p>Use the existing compression methods Gzip (extensions: tar.gz, tgz) instead.</p>
Impacts	Installations on ADK 4.8.x
Reasons for change	Installation time and RAM usage reduction
References	

## **glib-2 to be removed**

### **Status of change**

Type of change	Shared libraries removal. Gnome Input Output (libgio) will no longer be part of ADK release .
New behavior available	ADK 4.9.x
Planned Deprecation version	
ADK components	VOS-SYS
	The complete glib-2 bundle will no longer be provided in adk release.
	Backwards incompatible changes:
Changes	<ul style="list-style-type: none"> <li>• Any application linking statically or dynamically to one of the following will break: <ul style="list-style-type: none"> <li>○ libglib-2.0.so.0</li> <li>libgobject-2.0.so</li> <li>libgio-2.0.so</li> <li>libgmodule-2.0.so</li> <li>libgthread-2.0.so</li> </ul> </li> </ul>
Impacts	Upgrade to ADK 4.9.0
Reasons for change	DL file size reduction to ease migrations

## References

### **ICWK-encrypted data will be lost on downgrade**

#### **Status of change**

Type of change	ICWK encryption scheme will change. Downgrade from ADK 4.9 to older release would lead to loss of ICWK-encrypted data.
New behavior available	ADK 4.9.0, ADK 4.8.24, ADK 4.7.39
Planned Deprecation version	
ADK components	VOS-SEC
Changes	Backwards incompatible changes: <ol style="list-style-type: none"><li>1. ICWK-protected data will be re-encrypted upon upgrade</li><li>2. ICWK-protected data will be lost upon downgrade to older version<ol style="list-style-type: none"><li>1. Warranted keys (System keys)</li><li>2. AES DUKPT keys</li></ol></li></ol>
Impacts	Upgrade to ADK 4.9.0
Reasons for change	Vulnerability closed in ICWK

## References

### **Weak keys, weak certificate hashes prohibited by default for SSL/TLS**

#### **Status of change**

Type of change	Default configuration became more strict
New behavior available	ADK 4.8
<b>Planned Deprecation version</b>	<b>ADK 4.8.x</b>
ADK components	VOS-SEC, ADK-COM

- Changes
- ADK-COM default SSL\_POLICY will be updated to reject SSL/TLS connection with server authentication certificates:
    - With weak key sizes (e.g. RSA certificates<2048bits). Minimum RSA key size is 2048.
    - Signed using a weak hash (e.g. SHA1, MD5). Only algorithms from the SHA2 and SHA3 family are allowed.
  - Ciphers relying on SHA1, MD5 for MAC removed from OpenSSL default cipher list.
  - OpenSSL 1.0.2 X509\_verify\_cert() call behavior on VOS and VOS2 will now resemble the behavior for the same call from OpenSSL 1.1.1:
    - Following error codes were added from the upstream OpenSSL 1.1.1:
      - X509\_V\_ERR\_CA\_KEY\_TOO\_SMALL, error message "CA certificate key too weak"
      - X509\_V\_ERR\_CA\_MD\_TOO\_WEAK, error message "CA signature digest algorithm too weak"

- Impacts
- SSL/TSL connection.
  - Certificate verification with OpenSSL.

Reasons for change      PCI requirements.

PCI PTS 6 requirement:

- References
- TD9.2 In the case when certificates are used for server authentication, the tester shall execute tests to verify device behavior when receiving incorrect certificates, including:
- a) Expired certificates
  - b) Self-signed (un-authenticatable) certificate
  - c) Certificate with weak key size?e.g., RSA less than 2048 bits**
  - d) Certificate signed using a weak hash e.g., SHA1 or MD5**
  - e) Chaining error in certificate for cases a, b, c, or d

SSL\_POLICY: Please check the SSL policy chapter in the ADK programmers guide, section ADK COM for details.

## VOS2: "Fixed key" PIN encryption no longer allowed, single DES disabled by default

### Status of change

Type of change      Functionality removed

New behavior available	ADK 4.8
<b>Planned Deprecation version</b>	<b>ADK 4.8.x</b>
ADK components	VOS-SEC

In VOS2 IPP M/S the following changes apply:

Changes	<ul style="list-style-type: none"> <li>• Loading a master key with KeyUsage P0 is no longer allowed. P0 was required for 'Fixed Key' as the master key encrypts the PIN but now all master keys should have usage 'K0'.</li> <li>• M/S PIN encryption no longer supports 'Fixed Key'/ 'Zero GISKE session key'. So Bit5 of the IPP KMM no longer has any effect in IPP Packet Z60.</li> <li>• Using a single DES GISKE key for PIN encryption is no longer allowed. The session key must be 2key or 3key 3DES, otherwise Packet Z60 will return error '2', work key error.</li> <li>• Using a 'Key Only Format' (KOF) loaded key for PIN encryption is also no longer allowed. Again error '2', work key error, will be returned.</li> <li>• The default KMM for M/S is now 3DES.</li> </ul>
---------	--

Impacts	Key loading and key use for PIN encryption: Fixed key and single DES (see changes above for details)
---------	--

Reasons for change PCI 6 requirement

References

## Deprecated open source library headers: Fribidi

### Status of change

Type of change	Removal of deprecated fribidi library
New behavior available	ADK 4.6.0
Planned Deprecation version	ADK 4.7.0
ADK components	Open source library

Use of the private library fribidi is deprecated since ADK 4.6. The header files have been added back in ADK 4.7 for compatibility reasons, but are still considered private.

#### Changes

The library will be removed in a future version, including all header files without further notice,

#### Impacts

ADK 4.7.0

#### Reasons for change

- The library is private
- It is replaced with a different open source library in most components

#### References

## Limiting access to diagnostic API

### Status of change

#### Type of change

Limit access to OS API

#### New behavior available

ADK 4.8.0

#### Planned Deprecation version

ADK 4.8.0

#### ADK components

ADK-SYS, VOS-SEC, VOS-SYS

Access to the OS diagnostic API "diag\_counter\_get\_info" for regular users (usr1-15) is now restricted. Only system users (sys1-15) can access this information.

Use ADK-SYS APIs as an alternative to query system properties.

Values that are restricted:

Exposed by ADK:

- DIAG\_COUNT\_MSR\_READS\_ATTEMPTED
- DIAG\_COUNT\_MSR\_READS\_WITH\_ERRORS\_TRACK\_1
- DIAG\_COUNT\_MSR\_READS\_WITH\_ERRORS\_TRACK\_2
- DIAG\_COUNT\_MSR\_READS\_WITH\_ERRORS\_TRACK\_3
- DIAG\_COUNT\_MSR2\_READS\_WITH\_ERRORS\_TRACK\_1
- DIAG\_COUNT\_MSR2\_READS\_WITH\_ERRORS\_TRACK\_2
- DIAG\_COUNT\_MSR2\_READS\_WITH\_ERRORS\_TRACK\_3
- DIAG\_COUNT\_SMARTCARD\_INSERTIONS
- DIAG\_COUNT\_SMARTCARD\_ERRORS

Not exposed by ADK:

- [DIAG\_COUNT\_ID] = { "ID & Ver Maj,Min",OS,HEX,0,0 }
- [DIAG\_COUNT\_APPLICATION\_FIRST ... DIAG\_COUNT\_APPLICATION\_LAST] = { "App Counter",0,RESERVED,0,0 }
- [DIAG\_COUNT\_APPLICATION\_LAST+1 ... DIAG\_COUNTERS\_ALLOCATED-1] = { "OS Counter",0,RESERVED,0,0 },
- [DIAG\_COUNT\_NAND\_FLASH\_ECC\_ERRORS] = { "ECC Error",FLASH,SECRET,0,0 },
- [DIAG\_COUNT\_NAND\_FLASH\_ECC\_CORRECTED] = { "ECC Corrected",FLASH,SECRET,0,0 },

Impacts                   • access to OS API "diag\_counter\_get\_info"

Reasons for change       System vulnerabilities regarding usr1-15 access to secure side

References  
Please check the ADK programmers guide under sys info for more details

## **New user signing for V/OS2**

### **Status of change**

Type of change           • Introduction of new user signer cert tree for VOS2  
                              • Licence check for legacy VOS/VOS2 signer cards

New behavior available   ADK 4.8.0

Planned  
Deprecation version     ADK 4.8.0

ADK components   VOS-SEC

Changes                   • Introduction of new cert tree for VOS2 user signing  
                              • Added licence check for legacy VOS/VOS2 signer cards  
                              • Update 'crtreset' tool to handle new VOS2 user signing certs

Impacts                   • Installation of legacy signed application packages will fail, until a proper licence package containing the new VOS2 user signing certificate with matching sponsor was installed on the device  
                              • The licence packge with the new VOS2 user signing certificate has to be installed after upgrading to ADK 4.8 and before installing legacy signed application packages  
                              • Already installed applications will continue running after upgrade to ADK 4.8  
                              • New 'crtreset' tool has to be used with ADK 4.8  
                              • The changes only affect VOS2 platform. VOS is not affected.

Reasons for change	<ul style="list-style-type: none"> <li>• Separation of VOS and VOS2 application partition</li> <li>• Only clients with an approved <b>Software Licensing Agreement</b> will be able to sign and install applications</li> </ul>
	<p>Future outlook:</p> <ul style="list-style-type: none"> <li>• Enable Online Signing through Verifone Signing Portal</li> <li>• Retire physical signing cards after moving customers to Online Signing</li> </ul>
References	Please check the ADK programmers guide "Guidance for new user signing feature"

## **Filter environment variables passed to a process when starting it**

<b>Change</b>	<b>Filter environment variables passed to a process when starting it</b>
Status of change	
Type of change	<ul style="list-style-type: none"> <li>• Deprecation of unused functionality</li> </ul>
New behavior available	ADK 4.8.0
Planned Deprecation version	ADK 4.8.0
ADK components	V/OS
Changes	<ul style="list-style-type: none"> <li>• Added blacklist of dangerous environment variables that can NOT be passed to an app when invoked from another user app <ul style="list-style-type: none"> <li>◦ Blacklist applies to all 'usr' apps</li> </ul> </li> <li>• Added whitelist of allowed environment variables that can be passed to an app when invoked from another user <ul style="list-style-type: none"> <li>◦ Whitelist applies to all 'sys' apps</li> </ul> </li> </ul>
Impacts	<ul style="list-style-type: none"> <li>• usr apps can no longer pass dangerous environment variables from the blacklist to new processes</li> <li>• sys apps can only pass allowed environment variables from the whitelist to new processes</li> </ul>

Reasons for change

- Security improvement: Implement proper environment variable filtering using sudo. Allows to prevent certain attacks when new process is started with spoofed system environment variables.

Blacklist:

Environment variable	Description
IFS	
SHELL	
HOME	force-reset by -H or sudoers
LD_*	
PATH	
USER	force-reset by -u or sudoers
USERNAME	
OLDPWD	
PWD	

References

Whitelist:

Environment	Description
ADK_*	Prefix with the wildcard for future ADK environment variables.
GUI_REGION	ADK-GUI region id, which will be used to render application GUI
GUI_DISPLAY	If ARRS is active, this environment stores ARRS IP address and port for communication with Android unit.
MAC_APPID	Application id from manifest file
GUIPRT_APPNAME	Name of the resource folder from manifest file
SDISERVER	SDI server address

## Deprecate 'u' (user) engine keys

**Change**

**Deprecate 'u' (user) engine keys**

Status of change

Type of change

- Deprecation of unused functionality

New behavior available	ADK 4.8.0
Planned Deprecation version	ADK 4.8.0
ADK components	V/OS
Changes	<ul style="list-style-type: none"> <li>• "u" engine keys can no longer be installed to the VOS/VOS2 device</li> </ul>
Impacts	<ul style="list-style-type: none"> <li>• "u" engine keys that can only be installed with VRK</li> <li>• No users of "u" engine keys were found</li> </ul>
Reasons for change	<ul style="list-style-type: none"> <li>• According to PCI PTS K21 requirement unused and/or unnecessary functionality must be removed from the device.</li> </ul>
References	

## **Deprecate legacy Engage 2 piece solution**

<b>Change</b>	<b>Deprecate legacy 2 piece solution</b>
Status of change	
Type of change	Deprecation of Engage 2 piece solution in favor of using the SDI 2 piece solution
New behavior available	ADK 4.7.6
Planned Deprecation version	ADK 4.8.0
ADK components	ADK EMV
Changes	Support for legacy Engage 2 piece solution on Engage will be removed
Impacts	Users of the legacy implementation need to use ADK 4.6 and ADK 4.7 maintenance releases, and migrate to the SDI based solution in future
Reasons for change	The SDI based solution provides P2Pe certification and is available accross platforms including new Trinity devices
References	Please check the SDI programmers guide for details

## **ADK functions and OS APIs not used by ADC applications**

## Change

## Remove ADK functions & OS APIs no longer required.

Status of Change

Type of Change Removal of unused ADK functions and OS APIs from OS/ADK bundles.

New Behaviour ADK 4.6

Planned

Deprecation version ADK 4.6

ADK Components All ADK components. This will need to tie in with the other ADK changes on this page. The change also applies to the OS APIs in V/OS2.

Changes

- Removal of ADK functions no longer required / used
- Removal of OS APIs no longer required / used

Impacts

- Reduced time spent successfully delivering test scripts as part of the OS Quality Improvement project
- Smaller OS & ADK bundles - positive benefit to download / boot and extract times for OS/ADK stack in Manufacturing, Deployment & Repair.

Reason for Changes

- 391 ADK functions not used by ADC applications
- 2580 Private OS APIs not called directly by ADC applications (care required here as these APIs should only be called internally or by ADK functions)
- 244 Public OS APIs not called directly by ADC applications (care required here as additional APIs may be called indirectly by ADK functions called by ADC applications)
- Avoid unnecessary effort in creating unit tests for all ADK functions & OS APIs that are no longer in use.
- Remove unused code from OS/ADK bundles
- Improve OS/ADK download times
- Improve OS/ADK extraction times

Next Steps

## ADK-SEC-2.0 API changes

### Change

### Enhancement and restructuring of ADK-SEC

Status of change

Type of change New features and redesign of API library, configuration and security component

New behavior available ADK 4.5

Planned Deprecation version	ADK 4.8
ADK components	ADK-SEC
Changes	<ul style="list-style-type: none"> <li>• PIN entry functions removed</li> <li>• Changed API to reflect new features</li> <li>• More granular error codes</li> <li>• New configuration mechanism: flexible configurations by one JSON-formatted file, no dynamic changes (functions Sec_Set/GetSecurityConfig() are omitted)</li> <li>• Additional API functions for handling transaction data to provide encryption schemes with supplementary data</li> </ul>
Impacts	<ul style="list-style-type: none"> <li>• Users should use API functions with new interface (libsec.h)</li> <li>• Compatibility layer with ADK-SEC-1.5-interface (libseccmd.h) is provided for the time of migration. These API functions are not fully compatible to ADK-SEC-1.5 as some error codes and functions (Sec_SetSecurityConfig(), Sec_GetSecurityConfig()) are not supported. Old API functions in compatibility layer are marked with attribute 'deprecated' to generate compiler warning when using the old API functions.</li> <li>• Configuration was changed to a JSON-formatted file. ADK-SEC provides a conversion tool (on Windows) to convert legacy host configuration files to the JSON-formatted file.</li> </ul>
Reasons for change	<ul style="list-style-type: none"> <li>• Support of new encryption schemes (Voltage, Visa DSP, RSA)</li> <li>• Signing of ADK-SEC configuration file</li> <li>• Decoupling of Host and VSS script name</li> <li>• Extended key set ID for addressing more key sets</li> <li>• PIN input flexibility</li> </ul>
References	see ADK-SEC Programmers Guide especially section 'Migration Guide'

## EMV Client Library

<b>Change</b>	<b>Deliver EMV Client Library only as static library</b>
Status of change	
Type of change	<ul style="list-style-type: none"> <li>• Delivery format for EMV CT / CTLS Client Libraries</li> </ul>
New behavior available	ADK 4.4.0
Planned Deprecation version	ADK 4.5.0

ADK  
components

ADK Cards

- Changes
- Deliver EMV Client Library only as static library
  - Remove EMV client shared libraries from ADK.
  - Two different shared objects (local / client server) are replaced with one static library serving both + a new link shared object.
  - **Note:** This will only impact EMV CT/CTLS client libs, but not the EMV ADK framework or L2 kernel libraries (still delivered as shared libraries)
- Impacts
- Applications need to rebuild the application using the static variant for EMV CT and CTLS client libraries
  - Use Config API to drive the static lib in client/server or local mode.
  - Applications that bundled an already existing ADK EMV CT/CLTS client shared lib with their application do not need to recompile immediately, but should upgrade to the static lib variant once they use a new feature of ADK EMV.
- Reasons for change
- Users installed new ADK EMV client CT/CTLS shared libs with ADK integration packages and experienced incompatibilities. This has been because of the following:
    - ADK EMV guarantees source code compatibility but not binary compatibility. This means any extension to the APIs of ADK EMV CT and CTLS client will not require changes to existing application code, but changing the shared libraries for these client libs will break runtime compatibility.
    - However the compatibility between ADK CT/CTLS client and corresponding framework shared libraries is guaranteed. This means the ADK EMV CT/CLTS framework shared libraries can be changed in the system without recompiling the application that has linked to an older client library.
  - Due to this we recommend users to use only ADK EMV client static library during application binary compilation and linking.

References

## EMV Libraries Installation under System User

Change	EMV Libraries Installation under System User
Status of change	
Type of change	<ul style="list-style-type: none"><li>• Install all available EMV kernels under sys and let the user config decide which kernels to use</li><li>• Install the CTLS EMV framework component for VERTEX or VFI-Reader under sys</li><li>• Install the CT EMV framework component under sys</li></ul>
New behavior available	ADK 4.5.0

Planned  
Deprecation version ADK 4.5.0  
ADK components ADK Cards

Changes

- Remove the requirement to resign the VERTEX EMV kernels with apps signing cards but allow the app to select the needed kernels by config file instead.
- Move the EMV framework components to sys

Impacts

- Reorganization of the apps loading packages since VERTEX kernels can not be freely mixed
- New linking to be supported by app
- Providing config file for certified kernels to use is mandatory for the app. Only app knows which of the (now) all available kernels fits to their local certification

Reasons for change

- Apps complaints to resign the usr kernels with their apps signing cards and creating usr specific bundles on their own
- QA requires this process to support apps testing
- We need to add protection by config files to avoid that apps using wrong or not certified EMV kernels, which turned out difficult with letting themc reate their own apps kernel bundles

References

see Cards Services - EMV ADK Release Notes "How to migrate to system-signed EMV component"

see Cards Services - EMV Libraries Installation under System User

## **EMV Contactless Configuration Interface for Application Data**

<b>Change</b>	<b>EMV Contactless Configuration Interface for Application Data</b>
Status of change	
Type of change	<ul style="list-style-type: none"><li>• API deprecation</li></ul>
New behavior available	ADK 4.0
Planned API removal version	ADK 4.5.0
ADK components	ADK Cards

Changes	<ul style="list-style-type: none"> <li>• Replace global AID configuration with configuration per scheme</li> <li>• Remove older application data configuration API EMV_CTL5_SetAppliData()</li> </ul>
Impacts	<ul style="list-style-type: none"> <li>• Application AID configuration is now specific for the scheme. Only allowed parameter for the scheme can be used in the APIs.</li> <li>• Applications have to use the new API function EMV_CTL5_SetAppliDataSchemeSpecific() instead of EMV_CTL5_SetAppliData()</li> </ul>
Reasons for change	<ul style="list-style-type: none"> <li>• configuration data from more than 15 different CTLS kernels cannot be mapped to a single configuration parameter set anymore</li> <li>• old API EMV_CTL5_SetAppliData() has been marked as deprecated since ADK 4.0 already.</li> <li>• configuration for new kernels (e.g. Girocard, PagoBancomat, MIR) will no longer be supported with old API function EMV_CTL5_SetAppliData() starting with ADK 4.4.0</li> </ul>
References	see ADK EMV programmer's guide for details on the above mentioned configuration functions.

## EMV ADK - CTLS LED Handling

Change	EMV ADK - CTLS LED Handling
Status of change	
Type of change	Alternative API
New behavior available	ADK 4.3
Planned Deprecation version	
ADK components	ADK-EMV, ADK-GUI
Changes	<ul style="list-style-type: none"> <li>• With ADK 4.3 we are introducing an alternative way to show CTLS LEDs on screen.</li> </ul>
Impacts	<ul style="list-style-type: none"> <li>• Users should use the new ADK-GUI function to reserve part of the screen for LEDs ( uiShowLEDArea(),uiHideLEDArea() functions) and configure the LEDs layout ( uiConfigLEDs() function)</li> <li>• Users should use the existing ADK-EMV callback for LEDs and call the new ADK-GUI function to draw LEDs on screen ( uiSetLED() function )</li> </ul>

## Background:

- On devices w/o physical CTLS LEDs we are emulating those on screen. Due to tight time requirements this cannot be done via the ADK GUI server, but writing straight to the framebuffer to fulfill the timing requirements.
- So far we had the following options in ADK-EMV
  - A) getting a callback and the application can draw the LEDs itself
  - B) let ADK-EMV draw things on its own with limited styling options for the LEDs (only rectangular and circles).
- In some applications CTLS LEDs are required to blink outside the payment transaction ("idle blinking")

## Problem:

Reasons for change

- With introduction of Multi-App Controller (MAC) that allows switching between apps and shows CP apps, the direct framebuffer writing causes issues if the payment application doesn't turn this off before switching between applications. The net effect is that the LEDs will be drawn into other applications display regions.

## Solution:

- we have now implemented a new API in ADK-GUI to reserve a particular part of the screen for direct frame buffer access
- we have also added APIs to draw LEDs into the defined reserved regions allowing use of PNG image definitions for the LEDs in ON and OFF state. This make things look much nicer in fact.
- The reserved part of the screen will then not be overwritten with any other application content

References see ADK GUI reference guide for the LED Area handling

## Discontinue ADK Static Libraries

Change	Discontinue Static Libraries
Status of change	
Type of change	Remove ADK static libs for Verix and V/OS
New behavior available	ADK 4.2
Planned Deprecation version	ADK 4.5
ADK components	
Changes	<ul style="list-style-type: none"><li>• Remove ADK static libs from delivery and encourage users to use shared libraries</li></ul>

- VOS users have to link against .so files instead of .a files and install the .so file on the terminal
- Verix Users have to
  - use Verix VSA-type applications only with ADK
  - link against provide .so files instead of static libraries
  - download VLS-type shared libraries to the terminal
  - set the \*VSOPATH to reference the shared libs on the device correctly

Impacts

- Currently ADK has static libs are provided in the following formats for Verix:
  - no-pic: use with OUT and VSA applications
  - lib-pic: use to link with LIB shared lib files
  - vsl-pic: use to link with VSL shared lib files
- Also ADK supported VSL-type shared libraries for most of the components

With Verix OS QT000500 the Verix OS supports

Reasons for change

- - shared usage of code segments across processes with VSL-type shared libraries
  - dlopen/dlsym/dlclose for late binding that had been possible only with LIB-type libraries before

Due to this there are no need for static libraries any longer and we will retire them to reduce delivery packages and simplify deployment.

References see ADK Deployment Overview

## PIN Entry Handling via ADK-GUI

<b>Change</b>	<b>PIN Entry Handling via ADK-GUI</b>
Status of change	
Type of change	Remove deprecated API
New behavior available	ADK 3.1
Planned Deprecation version	ADK 4.3 (ADK-EMV), ADK 5.0 (ADK-SEC)
ADK components	ADK-EMV, ADK-SEC

- discontinue the support for PIN entry in EMV and SEC ADK components and replace this with a single PIN entry API for both offline and online PIN in ADK-GUI.
- This ADK-GUI API via html and properties has more flexibility and is more powerful to control PIN entry options and PIN entry prompt style. The ADK-GUI API is available since ADK 3.1.

Changes

Following functions will be discontinued:

Impacts

- ADK EMV: EMV\_CT\_EnterPIN() and EMV\_CTLN\_EnterPIN()
- ADK SEC: EnterAndEncryptPIN() and EnterAndHoldPIN()

These functions were originally introduced because Verix required to have PIN entry in the same task that later on processes the PIN.

Reasons for change

This restriction has been lowered in QT400 (in ADK 3.1) already and now we encourage the use of ADK-GUI for offline and online PIN entry.

We had put a note in the ADK-EMV / ADK-SEC release notes since ADK 3.1 that these APIs will be “will be removed after ADK 4.1.

References

see ADK GUI reference guide for PIN entry handling

## Product Overview - Branches

PCI Version: The PCI version listed is only the initially approved version. Please check the official PCI webpage for the currently approved version and availability of LOAs

<b>Product</b>	<b>Development branch</b>	<b>Release branch</b>	<b>Production branch</b>	<b>Active Maintenance</b>	<b>Sustain</b>
<b>UX115</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI N/A	ADK 4.8 (3161) PCI N/A	N/A
<b>V210</b>	ADK latest	ADK 5.1	ADK 5.0 (3241) PCI 6	ADK 4.8 (3161) PCI 6	N/A
<b>CM5</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>M440</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5

<b>M424</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>e280(v2)</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>V400m 4G</b>	ADK latest	ADK 5.1	ADK 5.0 (3241) PCI 6	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>V240m camera</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>e235</b>	ADK latest	ADK 5.1	ADK 5.0 (3241) PCI 6	ADK 4.8 (3161) PCI 6	N/A
<b>e285</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>M400</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>V240m V205c</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>V240 quectel</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5

<b>V400m</b>	ADK latest	ADK 5.1	ADK 5.0 (3241) PCI 6	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134)  PCI 5
<b>V200t</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134)  PCI 5
<b>P400 DMSR</b>	ADK latest	ADK 5.1	ADK 5.0 (3241) PCI 6	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>P200/P400/V200c</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>UX410</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>UX410 high mem MDB</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	N/A
<b>UX30x</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	ADK 4.7 (3134) PCI 5
<b>Ux30x high mem</b>	ADK latest	Not supported	ADK 5.0 (3241) PCI 5	ADK 4.8 (3161) PCI 5	N/A
<b>P630</b>	ADK latest	ADK 5.1	ADK 5.0 (Linux 4.9) PCI 6	N/A	N/A
<b>M425 / M450</b>	ADK latest	ADK 5.1	ADK 5.0 (Linux 4.9) PCI 6	N/A	N/A
<b>UX700 AIO / ML</b>	ADK latest	ADK 5.1	ADK 5.0 (Linux 4.9) PCI 6	N/A	N/A

**UX302**

ADK latest

ADK 5.1

ADK 5.0 (Linux  
5.15)  
PCI 6

N/A

N/A