



<https://verifone.cloud/docs/online-payments/getting-started/blocking-failed-3ds-transactions>

Updated: 24-Jun-2025

Blocking failed 3DS transactions

Overview

The purpose of 3-D Secure is to safeguard the online payment by applying an additional authentication step of the cardholder before sending an authorization request to the card issuer.

However, adoption of 3-D Secure is significantly different across geographic regions. This leads to a variety of payment flows, depending on if 3-D Secure is mandatory or not in that specific country.

Given the role of Verifone as a Payment Gateway, and the differences across regions where merchants can sell, it is necessary to add a blocking rule based on the result of the 3-D Secure authentication to enforce the business flow required by each country.

Availability

The **Blocking Rulesets** in Verifone Central is available under the *Administration* tab and can be used by any user with a Merchant Admin role.

Administration

Easily set up new accounts streamlined Account Setup process, optimize financial operations with our FinOps tools & fine-tune account with our Advanced Settings options.

The availability of 3D-Secure depends on each acquirer. Consult the list of supported acquirers together with the functionality available [here](#).

Workflow in Verifone Central

Merchants that fall under the requirements of PSD 2 and require a 3DS authentication from shoppers located inside the European Economic Area (EEA) need to create two blocking rules to block transactions that either failed or rejected the 3-D Secure authentication process.

Blocking rulesets must be set at Merchant Site level. As a Merchant Admin, in Verifone Central, go under **Administration > Blocking Rulesets** and create two new blocking rulesets, blocking based on the 3DS Authentication statuses: N (Failed) and R (Rejected). These need to be two independent blocking rulesets.

Create a blocking ruleset for failed 3DS transactions

Create ruleset

Name/Description

Block failed 3DS transactions

Organization

Parent

Apply to child organization(s)

No

Yes

Rules

3DS authentication status



is equal to



Failed (N)



Discard

Add Rule

Create ruleset

Create a blocking ruleset for rejected 3DS transactions

Create ruleset

Name/Description

Block rejected 3DS transactions

Organization

Parent

Apply to child organization(s)

No

Yes

Rules

3DS authentication status



is equal to



Rejected (R)



Discard

Add Rule

Create ruleset

Read the full documentation for blocking rulesets [here](#).

Reporting

Failed transactions due to blocking rulesets will have a response code = 9998 with the response description *Transaction blocked by validation rules*. Further reporting can be done based on the 3D Secure status N (Failed) and R (Rejected).